

## KLIPPON K5

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

### Similar to illustration



The aluminium Klippon® K enclosures are suitable for use in an extremely wide range of different areas. Various components can be installed inside the enclosures, and will benefit in particular from the high temperature resistance, the excellent IP protection and the good impact resistance.

No matter what kind of application the customer is planning, Weidmüller is able to provide a wide range of aluminium enclosures precisely fitting the customer's requirements.

Klippon® K enclosures for hazardous areas are available on request.

Our extensive product range offers the following advantages:

- Available in two surface finishes: natural and powder-coated (RAL 7001)
- With chloroprene moulded seal as standard (silicone moulded seal optionally available)
- Standardised closure system with Torx slotted screw head for 19 enclosure sizes
- Mounting holes outside of the gasket area
- High IP protection classes: IP66, IP67 and IP68 according to DIN EN 60529
- Impact resistance of up to 7 (10) Joules
- The enclosures are approved according ATEX, IECEx, EAC, cULus, Russian Maritime Register and DNV GL as well as the empty enclosure standard.

- Suitable for railway applications according to EN 45545-2:2013
- Alloy is resistant to salt water
- Standardised distributor enclosures with threaded holes and a variety of terminal configurations

### General ordering data

|                         |   |
|-------------------------|---|
| Version                 | Klippon K (aluminium empty enclosure), Empty enclosure, Aluminium enclosure, Height: 130 mm, Width: 170 mm, Depth: 90 mm, Material: Aluminium AISi12, untreated, silver |
| Order No.               | <a href="#">0342400000</a>  |
| Type                    | KLIPPON K5  |
| GTIN (EAN)              | 4008190075811   |
| Qty.                    | 1 pc(s).  |
| Unassembled to fit rail | <a href="#">1910080000</a>  |

## KLIPPON K5

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## Dimensions and weights

|                             |         |                            |            |
|-----------------------------|---------|----------------------------|------------|
| Depth                       | 90 mm   | Depth (inches)             | 3.543 inch |
| Height                      | 130 mm  | Height (inches)            | 5.118 inch |
| Width                       | 170 mm  | Width (inches)             | 6.693 inch |
| Mounting dimension - height | 110 mm  | Mounting dimension - width | 150 mm     |
| Net weight                  | 1,360 g |                            |            |

## Temperatures

Operating temperature -40 °C...80 °C

## Environmental Product Compliance

REACH SVHC Lead 7439-92-1

## Cable glands, left

|     |   |     |   |
|-----|---|-----|---|
| M12 | 4 | M16 | 2 |
| M20 | 1 | M25 | 1 |
| M32 | 1 |     |   |

## Cable glands, right

|     |   |     |   |
|-----|---|-----|---|
| M12 | 4 | M16 | 2 |
| M20 | 1 | M25 | 1 |
| M32 | 1 |     |   |

## Cable glands, top/bottom

|     |    |     |   |
|-----|----|-----|---|
| M12 | 11 | M16 | 8 |
| M20 | 4  | M25 | 3 |
| M32 | 2  |     |   |

## Certificate numbers enclosure

|   |   |  |                      |
|---|---|--|----------------------|
| Approval conditions                     | cULus, RMRS, DNV                          | Certificate No. (DNVGL)                | TAE00002SM           |
| Certificate No. (EAC)                   | C-DE.HB07.B.00089-20                      | Certificate No. (GERMLLOYD)            | TAE00002SM           |
| Certificate No. (MARITREG)              | 19.00108.272                              | Certificate no. (cULus)                | E197061              |
| Certificate no. Terminal Box (EAC)      | C-DE.AD54.B.00251/19<br>Ind. Terminal Box | Certificate no., empty enclosure (EAC) | C-DE.HB07.B.00089/20 |
| Declaration of Conformity No. (DoC LVD) | DE_PS2410_160412_001ISS01                 |  |                      |

## KLIPPON K5

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## General information

|                             |  |                                 |                                     |
|-----------------------------|--|---------------------------------|-------------------------------------|
| Access opening: height      | 120.8 mm   | Access opening: width           | 160.8 mm                            |
| Areas of use                | Process industry, Transportation, Marine engineering, Packaging industry, Harbour facilities, Machine construction | Enclosure attachment            |                                     |
| Flange plate                | No   | Impact resistance               | Holes 6 mm<br>10 J version standard |
| Integral fixing             | Threaded holes M5  | Lid                             | Yes                                 |
| Lid attachment              | M5 torx stainless steel screws with slot   | Material                        | Aluminium AlSi12                    |
| Material thickness of cover | 3 mm   | Material thickness of enclosure | 4.6 mm                              |
| Note: protection class      | IP68 (t=72h, h=1m)   | Number of lid screws            | 4                                   |
| Operating temperature, max. | 80 °C  | Operating temperature, min.     | -40 °C                              |
| Protection class (UL)       | Type 4, Type 4x  | Protection degree               | IP66, IP67, IP68                    |
| Seal material               | Chloroprene  | Standards                       | EN 45545-2:2013                     |
| Surface finish              | untreated  | Torque for lid screws           | 2.5 Nm                              |

## horizontal assembly

|                             |      |                 |      |
|-----------------------------|------|-----------------|------|
| WDU 10 / ZDU 10             | 1x10 | WDU 16 / ZDU 16 | 1x8  |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 1x20 | WDU 4 / ZDU 4   | 1x17 |
| WDU 6 / ZDU 6               | 1x12 |                 |      |

## vertical assembly

|                             |   |               |   |
|-----------------------------|---|---------------|---|
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | * | WDU 4 / ZDU 4 | * |
|-----------------------------|---|---------------|---|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000261    | ETIM 7.0    | EC000261    |
| ETIM 8.0    | EC000261    | ECLASS 9.0  | 27-18-01-01 |
| ECLASS 9.1  | 27-18-92-90 | ECLASS 10.0 | 27-18-01-01 |
| ECLASS 11.0 | 27-18-01-01 | ECLASS 12.0 | 27-18-01-01 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E197061 |

**KLIPPON K5**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**

**Downloads**

|   |  |
|---|--|
| Approval/Certificate/Document of Conformity | <a href="#">C-DE.A154.B.00251.19 Ind. Terminal Box</a><br><a href="#">RUC-DE.BE02.B.00173</a><br><a href="#">TAE00002SM</a><br><a href="#">19.00108.272</a><br><a href="#">EU Declaration of Conformity - Klippon K Empty Enclosures - DoC DE PS2410 160412 001ISS02</a><br><a href="#">DoM Klippon K salt water resistance</a><br><a href="#">DoM Klippon K EN 45545-2 2013 Railway</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>  |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>   |
| Tender specification                        | <a href="#">Klippon K5_0342400000_DE</a><br><a href="#">Klippon K5_0342400000_EN</a>   |
| User Documentation                          | <a href="#">Assembly guidelines - empty enclosures</a>   |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>   |
| Brochures                                   | <a href="#">MB KLIPPON ENCL.TECN EN</a><br><a href="#">FL RAILWAY 2014 EN</a><br><a href="#">FL RAILWAY 2014 EN</a>  |

**KLIPPON K5**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**Drawings**

**Dimensioned drawing**

