

TS 35X7.5 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Similar to illustration

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Rail, TS 35, TS 35 x 7.5, without slot, Steel, galvanic zinc plated and passivated
Order No.	0383400000
Type	TS 35X7.5 2M/ST/ZN
GTIN (EAN)	4008 190088026
Qty.	2 m

Creation date May 20, 2022 3:16:06 PM CEST

Catalogue status 06.05.2022 / We reserve the right to make technical changes.

TS 35X7.5 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	7.5 mm	Depth (inches)	0.295 inch
Height	35 mm	Height (inches)	1.378 inch
Width	2,000 mm	Width (inches)	78.74 inch
Net weight	325 g		

Mounting rail

Installation advice	Direct mounting		
Length of the terminal rail	min.	0 mm	
	nominal	2,000 mm	
	max.	2,000 mm	
Material	Steel		
Pre-punched mounting rail	No		
Short circuit strength corresponds to E-Cu wire	16 mm ²		
Short-time withstand current according to IEC 60947-7-2	1.92 kA/1s		
Slit gap			
Slit length			
Slit width			
Standards	DIN EN 60715		
Surface finish	galvanic zinc plated and passivated		
Thickness	1 mm		

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02	ECLASS 12.0	27-40-06-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	