

COMBI® Junction boxes



COMBI® 206



- Protection class: IP66 / IP67
- Glow wire test: 750 °C
- Temperature range: -30 °C - 100 °C
- Installation temperature: -5 °C - 60 °C
- Voltage: 400 V
- Material: Polypropylen, Gasket TPE
- Dimensions: 85 x 49 x 51 mm

Remarks: .../5 = Clamping cage 5-poles
 .../3x WAGO 221-413 = incl. 3 WAGO terminals 221-413

Type	RAL 7035 LG	RAL 9005 BK	RAL 9001 WH	VPE
COMBI® 206	10109569	10109571	10109573	10
COMBI® 206/5	10109570	10109572	10109574	10
COMBI® 206 / 3xWAGO 221-413	10109901	10109900	10109902	10



COMBI® 308



- Protection class: IP66 / IP67
- Glow wire test: 750 °C
- Temperature range: -30 °C - 100 °C
- Installation temperature: -5 °C - 60 °C
- Voltage: 400 V
- Material: Polypropylen, Gasket TPE
- Dimensions: 85 x 85 x 51 mm
- Incl. SMB = Mounting clip for snap-on fixing

Remarks: .../5 = Clamping cage 5-poles
 .../3-221-413 = incl. 1 WAGO terminal holder and
 3 WAGO terminals 221-413

Type	RAL 7035 LG	RAL 9005 BK	RAL 9001 WH	RAL 7035 / LG RAL 3000 / RD*	VPE
COMBI® 308	10060400	10060581	10060610	10060480	5
COMBI® 308/5	10060401	10060580	10060611	10107390	5
COMBI® 308 / 3-221-413	10110403	10110404	10110405		5

*See page 6