


CP DC BUFFER 24V 20A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com



The Weidmüller DC buffer module is a supplementary system component for 24 V DC power system which can be used for various purposes. It delivers DC-power to bridge mains failures of the DC voltage system and can extend the hold-up time after loss of the mains power. The service-free electrolytic capacitors allow the continuous operation at ambient temperatures up to +70°C. It can also be operated in parallel to increase a longer bridging time or the output power.

General ordering data

Version	Buffer module, 30 V, 24 V
Order No.	1251220000
Type	CP DC BUFFER 24V 20A
GTIN (EAN)	4050118043174
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2021-12-31
Alternative product	2786240000

Creation date May 22, 2022 1:59:55 PM CEST

CP DC BUFFER 24V 20A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	150 mm	Depth (inches)	5.905 inch
Height	130 mm	Height (inches)	5.118 inch
Width	66 mm	Width (inches)	2.598 inch
Net weight	1,274 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-25 °C...70 °C
Humidity	5...95 %, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Rated data UL

Certificate No. (cURus)	E349964
-------------------------	---------

Input

Connection system	Screw connection	Input current	0...22 A
Input voltage, max.	30 V	Input voltage, min.	22.5 V
Max. approved input current	22 A	Rated input voltage	24 V DC
Surge protection	31 - 34 V (only at discharge)		

Output

Output current	20A	Output current, max.	22 A
Output voltage, note	Corresponds to the input voltage	Overload protection	≥ 22 A (only at discharge)
Parallel connection option	Yes, without diode module	Surge protection	31 - 34 V (only at discharge)

General data

Buffer times	250 ms at 20 A, 6 s at 1 A	Clip-in foot	metal
Degree of efficiency	95 %	Humidity	5...95 %, no condensation
Max. perm. air humidity (operational)	5 %...95 % RH	Operating temperature	-25 °C...70 °C
Storage medium	Internal condenser		

EMC / shock / vibration

Interference immunity test acc. to	EN 61000-4-2 (ESD), EN 61000-4-3 and EN 61000-4-8 (fields), EN 61000-4-4 (burst)	Noise emission in accordance with EN55032	Class B
------------------------------------	---	--	---------

Insulation coordination

Insulation voltage, input/output	1 kV
----------------------------------	------

CP DC BUFFER 24V 20A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Electrical safety (applied standards)

For use with electronic equipment Acc. to EN50178 /
VDE0160

Connection data (input)

Conductor cross-section, AWG/kcmil , max.	6	Conductor cross-section, AWG/kcmil , min.	26
Conductor cross-section, flexible , min.	0.5 mm ²	Conductor cross-section, rigid , max.	16 mm ²
Conductor cross-section, rigid , min.	0.5 mm ²	Connection system	Screw connection
Wire connection cross section, flexible (input), max.	16 mm ²		

Connection data (output)

Conductor cross-section, AWG/kcmil , max.	6	Conductor cross-section, AWG/kcmil , min.	26
Conductor cross-section, flexible , max.	16 mm ²	Conductor cross-section, flexible , min.	0.5 mm ²
Conductor cross-section, rigid , max.	16 mm ²	Conductor cross-section, rigid , min.	0.6 mm ²

Connection data (signal)

Wire connection method	Screw connection	Wire cross-section, AWG/kcmil , max.	15
Wire cross-section, AWG/kcmil , min.	30	Wire cross-section, solid , max.	1.5 mm ²
Wire cross-section, solid , min.	0.2 mm ²		

Signalling

Status indicator	Status relay (max. load)	Input voltage OK (30 V AC/DC 2A), Ready for operation (24 V AC/DC 300 mA)
Green LED		

Approvals

Certificate No. (cURus)	E349964	Institute (cURus)	CURUS
-------------------------	---------	-------------------	-------

Classifications

ETIM 6.0	EC002850	ETIM 7.0	EC002850
ETIM 8.0	EC002850	ECLASS 9.0	27-04-06-92
ECLASS 9.1	27-04-92-01	ECLASS 10.0	27-04-06-92
ECLASS 11.0	27-04-06-92	ECLASS 12.0	27-04-06-92

Approvals

Approvals



ROHS	Conform
UL File Number Search	E349964

CP DC BUFFER 24V 20A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

Approval/Certificate/Document of Conformity	DE_PA5200_160510_001.pdf
Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Operating instructions
Catalogues	Catalogues in PDF-format
Brochures	
