

**CableLine  
CLI M 2-4 GE/SW U MP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

CLI M identification markers are slid onto CLI MH carrier strips and secured by means of cable ties. The system is particularly suitable for large conductor and cable cross-sections.

Advantages:

- Combination marker for cable and pipe markers
- One size for all diameters above 16 mm<sup>2</sup>
- Unrestricted combination options
- Closed, permanently attached markers
- Very good legibility

**General ordering data**

|            |  |
|------------|--|
| Type       | CLI M 2-4 GE/SW U MP   |
| Order No.  | <a href="#">1733651679</a>   |
| Version    | CableLine, Conductor and cable markers, 10 - 317 mm, 4 x 11.3 mm, yellow |
| GTIN (EAN) | 4008 190398255   |
| Qty.       | 100 pc(s).   |

Creation date July 8, 2020 11:08:17 AM CEST

Catalogue status 08.07.2020 / We reserve the right to make technical changes.

## CableLine CLI M 2-4 GE/SW U MP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 11.3 mm | Width (inches)  | 0.445 inch |
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Depth      | 3 mm    | Depth (inches)  | 0.118 inch |
| Net weight | 0.12 g  |                 |            |

### General data

|  |                    |                             |                            |
|--|--------------------|-----------------------------|----------------------------|
| Colour                                       | yellow             | Colour of printing          | black                      |
| Halogen                                      | Yes                | Material                    | PVC, soft, without Cadmium |
| Material colour according to resistance code | 4                  | Operating temperature range | -30...80 °C                |
| Orientation of print                         | horizontal         | Printed characters          | Upper-case letters         |
| Printing                                     | U                  | Printing method             | hot-embossing              |
| Recommended industries                       | Process, Machinery | Type of printing            | Standard                   |
| UL 94 flammability rating                    | V-0                | Version                     | MultiPack                  |
| Width  | 11.3 mm            |                             |                            |

### Conductor and cable markers

|                               |                    |                               |                     |
|-------------------------------|--------------------|-------------------------------|---------------------|
| Conductor O.D.                | 10 - 317 mm        | Conductor O.D., max.          | 317 mm              |
| Conductor O.D., min.          | 10 mm              | Conductor cross-section, max. | 500 mm <sup>2</sup> |
| Conductor cross-section, min. | 16 mm <sup>2</sup> | Halogen                       | Yes                 |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC     | 44-12-17-08 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">EPLAN, WSCAD</a>   |
| Product Change Notification | <a href="#">PCN CableLine_DE</a><br><a href="#">PCN CableLine_EN</a> |

**Data sheet**

**CableLine  
CLI M 2-4 GE/SW U MP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**



Similar to illustration