

CableLine CLI TM 20-33

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



CLI TM is the right sleeve for large conductor cross-sections. The sleeve's transparent pocket protects the inlay tags against environmental influences. Cable ties are used to fix the transparent CLI TM sleeve in place. Marking is carried out with TM-I 18 for CLI TM 10/33 or ESG 9/17 for CLI TM20/33. Both inlay tags are designed in the proven MultiCard format and can be comfortably labelled with SMark laser, PrintJet, plotter or MC-Mobilo. The CLI F 2/17,5 tag is suitable for CLI TM 20/66.

- Secure attachment with cable ties
- Professional labelling thanks to Weidmüller's marking devices for MultiCards

General ordering data

Type	CLI TM 20-33
Order No.	1763280000
Version	CableLine, Conductor and cable markers, 10 - 317 mm, 33 x 11.3 mm, Transparent
GTIN (EAN)	4032248050246
Qty.	100 pc(s).

Creation date July 8, 2020 11:08:23 AM CEST

Data sheet

CableLine CLI TM 20-33

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	11.3 mm	Width (inches)	0.445 inch
Height	33 mm	Height (inches)	1.299 inch
Depth	5 mm	Depth (inches)	0.197 inch
Net weight	0.7 g		

General data

Colour	Transparent	Halogen	Yes
Material	PVC	Operating temperature range	-30...60 °C
Recommended industries	Process, Machinery	Type of printing	neutral
UL 94 flammability rating	V-0	Width	11.3 mm

Conductor and cable markers

Conductor O.D.	10 - 317 mm	Conductor O.D., max.	317 mm
Conductor O.D., min.	10 mm	Conductor cross-section, max.	500 mm ²
Conductor cross-section, min.	16 mm ²	Halogen	Yes

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
eClass 9.0	27-40-04-01	eClass 9.1	27-40-04-01
eClass 10.0	27-40-04-01	UNSPSC	44-12-17-08

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
------------------	------------------------------