

TM
TM 201/18 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Similar to illustration

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

| | |
|------------|---|
| Type | TM 201/18 V0 |
| Order No. | 1798600000 |
| Version | TM, Socket x 5 mm, PVC, Colour: Transparent, Conductor O.D.: 1.5 - 2.5 mm |
| GTIN (EAN) | 4032248243341 |
| Qty. | 1,000 pc(s). |

Creation date July 8, 2020 11:09:15 AM CEST

Catalogue status 08.07.2020 / We reserve the right to make technical changes.

Data sheet

TM
TM 201/18 V0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Width | 5 mm | Width (inches) | 0.197 inch |
| Height | 18 mm | Height (inches) | 0.709 inch |
| Depth | 5 mm | Depth (inches) | 0.197 inch |
| Net weight | 0.37 g | | |

General data

| | | | |
|-----------------------------|-------------|---------------------------|---------------------------|
| Colour | Transparent | Material | PVC |
| Operating temperature range | -40...80 °C | Recommended industries | Transportation, Machinery |
| Type of printing | neutral | UL 94 flammability rating | V-0 |
| Width | 5 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|----------------------|-------------------------------|---------------------|
| Conductor O.D. | 1.5 - 2.5 mm | Conductor O.D., max. | 2.5 mm |
| Conductor O.D., min. | 1.5 mm | Conductor cross-section, max. | 1.5 mm ² |
| Conductor cross-section, min. | 0.25 mm ² | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC | 44-12-17-08 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| Product Change Notification | PCN Transparent Sleeves_DE PCN Transparent Sleeves_EN |