

SAIB-M8-3P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

General ordering data

Version	Field attachable connector, M8, Female socket, straight
Order No.	1803870000
Туре	SAIB-M8-3P
GTIN (EAN)	4032248259854
Qty.	1 pc(s).



SAIB-M8-3P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	10 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data customisable plug-in connectors

Cable diameter	3.55 mm	Cable diameter, max.
Cable diameter, min.	3.5 mm	Coding
Conductor cross-section, max.	0.5 mm ²	Conductor cross-section
Connection cross-section, max.	0.5 mm ²	Connection cross-section
Contact surface	Gold-plated	Housing main material
Insulation strength	10 ⁸ Ω	Number of poles
Plugging cycles	≥ 50	Pollution severity
Protection degree	IP67	Rated current
Rated voltage	60 V	Rated voltage
Shield connection	No	Temperature range of ho
Threaded ring material	Diecast zinc	Type of connection

Cable diameter, max.	5 mm
Coding	none, A
Conductor cross-section, min.	0.14 mm ²
Connection cross-section, min.	0.14 mm ²
Housing main material	PA
Number of poles	3
Pollution severity	3
Rated current	4 A
Rated voltage	60 V
Temperature range of housing	-40 +85 ° C
Type of connection	Screw connection

Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ETIM 8.0	EC002635	ECLASS 9.0	27-44-01-02
ECLASS 9.1	27-44-01-03	ECLASS 10.0	27-44-01-02
ECLASS 11.0	27-44-01-02	ECLASS 12.0	27-44-01-16

Approvals

Approvals



ROHS	Conform
UL File Number Search	E307231

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	<u>Manual</u>
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN
	<u>FL FIELDWIRING EN</u>