

CLI M 2-40Q GE NE SG



General ordering data

Version	CableLine, Conductor and cable markers, 10 - 317 mm, 4 x 11.4 mm, yellow
Order No.	1886541687
Type	CLI M 2-40Q GE NE SG
GTIN (EAN)	4032248491964
Qty.	500 pc(s).

Dimensions and weights

Depth	3 mm
Depth (inches)	0.118 inch
Height	4 mm
Height (inches)	0.157 inch
Width	11.4 mm
Width (inches)	0.449 inch
Net weight	1.046 g

Temperatures

Operating temperature range	-30...80 °C
-----------------------------	-------------

General data

Colour	yellow
Halogen	Yes
Material	PVC, soft, without Cadmium
Material colour according to resistance	4

code	
Number of markers per combination	1 Component part = Conductor and cable markers
Operating temperature range	-30...80 °C
Operating temperature range, max.	80 °C
Operating temperature range, min.	-30 °C
Printing	Blank
Recommended industries	Process, Machinery
Type of printing	neutral
UL 94 flammability rating	V-0
Version	Loop
Width	11.4 mm

Conductor and cable markers

Conductor O.D.	10 - 317 mm
Conductor O.D., max.	317 mm
Conductor O.D., min.	10 mm
Conductor cross-section, max.	500 mm ²
Conductor cross-section, min.	16 mm ²
Cross-section for connected wire	16 - 500 mm ²
Halogen	Yes

Downloads

Engineering Data	<u>EPLAN, WSCAD</u>
Product Change Notification	<u>PCN CableLine_DE</u> <u>PCN CableLine_EN</u>
Catalogues	<u>Catalogues in PDF-format</u>

Classifications

ETIM 6.0	EC001530
ETIM 7.0	EC001530
ETIM 8.0	EC001530
ECLASS 9.0	27-40-04-01
ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01
ECLASS 11.0	27-28-11-02
ECLASS 12.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Related products:



Order No.: 1395680000
Type: CLI M 2-40Q NE MP

Version:
CableLine,
Conductor and
cable markers, 10 -
317 mm, 4 x 11.4
mm

[PDF data sheet](#)
[Add to Inquiry List](#)