

CLI T 3-30



General ordering data

Version	CableLine, Socket x 5 mm, PVC, Colour: Transparent, Conductor O.D.: 8 - 16 mm
Order No.	1889550000
Type	CLI T 3-30
GTIN (EAN)	4032248496358
Qty.	100 pc(s).

Dimensions and weights

Height	30 mm
Height (inches)	1.181 inch
Width	5 mm
Width (inches)	0.197 inch
Net weight	2.1 g

Temperatures

Operating temperature range	-30...80 °C
-----------------------------	-------------

General data

Colour	Transparent
Halogen	Yes
Material	PVC
Operating temperature range	-30...80 °C
Operating temperature range, max.	80 °C
Operating temperature range, min.	-30 °C

Recommended industries	Transportation, Machinery
UL 94 flammability rating	V-0
Width	5 mm

Conductor and cable markers

Conductor O.D.	8 - 16 mm
Conductor O.D., max.	16 mm
Conductor O.D., min.	8 mm
Conductor cross-section, max.	75 mm ²
Conductor cross-section, min.	25 mm ²
Cross-section for connected wire	25 - 75 mm ²
Halogen	Yes

Downloads

Engineering Data	<u>EPLAN, WSCAD</u>
Product Change Notification	<u>PCN Transparent Sleeves DE</u> <u>PCN Transparent Sleeves EN</u>
Catalogues	<u>Catalogues in PDF-format</u>

Classifications

ETIM 6.0	EC001530
ETIM 7.0	EC001530
ETIM 8.0	EC001530
ECLASS 9.0	27-40-04-01
ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01
ECLASS 11.0	27-28-11-02
ECLASS 12.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Related products:



Order No.: 1889580000
Type: CLI T 02-30

Version:
CableLine, Socket x
5 mm, PVC, Colour:
Transparent,
Conductor O.D.: 1.3
- 3 mm

[PDF data sheet](#)
[Add to Inquiry List](#)

Type: CLI T 1-30



CableLine, Socket x
5 mm, PVC, Colour:
Transparent,
Conductor O.D.: 2.5
- 5 mm

[PDF data sheet](#)
[Add to Inquiry List](#)

Order No.: 1889570000

Type: CLI T 2-30



Version:
CableLine, Socket x
5 mm, PVC, Colour:
Transparent,
Conductor O.D.: 4 -
10 mm

[PDF data sheet](#)
[Add to Inquiry List](#)