

**ZQV 1.5N/20****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Order No.  | <a href="#">1985600000</a> |
| Type       | ZQV 1.5N/20                |
| GTIN (EAN) | 4050118370225              |
| Qty.       | 20 pc(s).                  |

**ZQV 1.5N/20****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 2.8 mm  | Depth (inches)  | 0.11 inch  |
| Height     | 21.9 mm | Height (inches) | 0.862 inch |
| Width      | 70 mm   | Width (inches)  | 2.756 inch |
| Net weight | 6.52 g  |                 |            |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | orange |
| UL 94 flammability rating | V-0   |        |        |

**Additional technical data**

|                          |    |                |         |
|--------------------------|----|----------------|---------|
| Explosion-tested version | No | Type of fixing | Plugged |
|--------------------------|----|----------------|---------|

**Cross-connector**

|                       |        |                           |        |
|-----------------------|--------|---------------------------|--------|
| Rated current, 2-pole | 17.5 A | Rated current, multi-pole | 17.5 A |
|-----------------------|--------|---------------------------|--------|

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 3.5 mm |
|-----------------|--------|

**General**

|                 |    |
|-----------------|----|
| Number of poles | 20 |
|-----------------|----|

**Rating data**

|               |        |
|---------------|--------|
| Rated current | 17.5 A |
|---------------|--------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |

**Important note**

|                     |   |
|---------------------|---|
| Product information | Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used |
|---------------------|---|

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date May 17, 2022 4:36:30 PM CEST

Catalogue status 06.05.2022 / We reserve the right to make technical changes.

**Data sheet****ZQV 1.5N/20**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Downloads**

---

|   |   |
|---|---|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>   |
| Engineering Data                            | <a href="#">CAD data – STEP</a>   |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>  |
| User Documentation                          | <a href="#">2434520000_BED-ANL_ZQV_A_REIHE.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a><br><a href="#">BPZL ZQV 2.5</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>  |
| Brochures                                   |   |

---