



Klemmsan[®]

270270 CPR-16

Current Monitoring Relay

General	Casing Width (mm)	36
	Connections	Screw Terminal
	Network	-
	Response Time for Monitoring Any Function	Maks. 100ms
	Type of Output	Relay
	Supply Frequency	35-70Hz
	Control Input Voltage Range	Same with supply voltage
	Operating Frequency	35-70Hz
	Protection Class	IP20
	Mounting Type	Panel or Rail
	EMC-EMI	✓
	Packing Unit	1
	Weight (g)	95
	Packing Unit	
Dimensions	—	
Phase Failure	Fixed Delay Time	-
Phase Sequence	Fixed Delay Time	-
Adjustable/Fixed Unbalanced Protection	Range/Limit	-
	Hysteresis	-
	Delay Time	-
Adjustable Voltage Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-

	Delay Time	-
Adjustable Current Protection	Upper Limit	1 => 16AAC arası
	Lower Limit	-
	Hysteresis	5 => 20% x Upper limit
	Delay Time	0.1 => 10 sec
Adjustable Frequency Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-
	Delay Time	-
Adjustable/Extremely High-Low Voltage Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-
	Delay Time	-
PTC Protection	Fixed Delay Time	-
	Threshold	-
Auxiliary Contacts	Type	1 C/O (SPDT)
	Max. Ratings - AC (for NO Side)	16A/250V;4000VA
	Max. Ratings - DC (for NO Side)	-
	Mechanical Lifetime	$\geq 10^7$ operation
	Electrical Lifetime Operations (for NO Side)	1×10^5
Supply Voltage	DC	24-300VDC
	AC	36-300VAC
Ambient Conditions	Operating Temperature	-20°C +60°C
	Storing Temperature	-40°C +75°C
	Relative Humidity (No Condensation)	Maks. 95% (no condensation)
Power Consumption	DC	<1W
	AC	<3VA

Order Info

270270 Current Monitoring Relay

