SIEMENS

Data sheet 3SB2000-2EE01



Selector switch, 16 mm, round, plastic, green, 3 switch positions I>O<II, momentary contact type, Retraction from left and right, Actuating angle 2 x 50 degree

Figure similar

product designation design of the product product type designation SB2 Enclosure number of command points Actuator design of the actuating element principle of operation of the actuating element product extension optional light source color of the actuating element material of the actuating element pulsatic outer diameter of the actuating element type of unlocking device number of switching positions actuating angle e clockwise e anticlockwise Front ring product component front ring Selector switch 1 Actuation memerary contact type momentary contact type No product component front ring Selector switch assertion 1 Actuator design of the actuating element momentary contact type No selector switch momentary contact type product extension optional light source No selector switch momentary contact type product system selector switch momentary contact type No solector switch without 19 mm without 19 mm type of unlocking device solector switch yes
product type designation 3SB2 Enclosure number of command points 1 Actuator design of the actuating element selector switch principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise • anticlockwise • anticlockwise Front ring
Enclosure number of command points Actuator design of the actuating element selector switch principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise • anticlockwise Front ring
number of command points Actuator design of the actuating element selector switch principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise • anticlockwise Front ring
Actuator design of the actuating element selector switch principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise 50° • anticlockwise 50° Front ring
design of the actuating element principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element type of unlocking device number of switching positions actuating angle clockwise anticlockwise front ring
principle of operation of the actuating element momentary contact type product extension optional light source No color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise 50° • anticlockwise 50° Front ring
product extension optional light source color of the actuating element material of the actuating element outer diameter of the actuating element type of unlocking device number of switching positions actuating angle clockwise anticlockwise anticlockwise Front ring
color of the actuating element green material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle • clockwise 50° • anticlockwise 50° Front ring
material of the actuating element plastic outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 3 actuating angle
outer diameter of the actuating element type of unlocking device number of switching positions actuating angle clockwise anticlockwise outer diameter of the actuating element without 3 actuating angle outer diameter of the actuating element in the sum of the s
type of unlocking device without number of switching positions 3 actuating angle • clockwise 50° • anticlockwise 50° Front ring
number of switching positions actuating angle • clockwise • anticlockwise Front ring
actuating angle • clockwise • anticlockwise 50° Front ring
 clockwise anticlockwise 50° 50° Front ring
• anticlockwise 50° Front ring
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
Holder
material of the holder Plastic
General technical data
product function
• EMERGENCY OFF function No
• EMERGENCY STOP function No
protection class IP IP65
operating frequency maximum 1 000 1/h
mechanical service life (operating cycles) typical 300 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
Connections/ Terminals
tightening torque of the screws in the bracket 0.4 N·m
Ambient conditions
ambient temperature
• during operation -25 +70 °C

during storage	-40 +80 °C
environmental category during operation according to IEC 60721	3K6
Installation/ mounting/ dimensions	
fastening method	front plate mounting
shape of the installation opening	round
mounting diameter	16 mm
mounting height	17 mm
installation width	19 mm
installation depth	50 mm
Approvals Certificates	



General Product Approval







Declaration of Conformity



Miscellaneous

Test Certificates

Test Certificates

other

Special Test Certificate

Type Test Certificates/Test Report

Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2000-2EE01

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2000-2EE01

 $Service \& Support \ (Manuals, \ Certificates, \ Characteristics, \ FAQs, ...)$

https://support.industry.siemens.com/cs/ww/en/ps/3SB2000-2EE01

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2000-2EE01&lang=en

		_
last modified:	1/26/2022	7