SIEMENS

Data sheet

3SB2000-4PA01



Key-operated switch, 16 mm, round, plastic, CES, SB2, 3 switch positions I-O-II, latching, Actuating angle 2 x 62 degree key removal O, possible special locks: SB3, SB4, SB5

Figure similar	
product brand name	SIRIUS
product designation	Key-operated switches
design of the product	Single device round
product type designation	3SB2
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Key-operated switch
principle of operation of the actuating element	latching
product extension optional light source	No
material of the actuating element	plastic
outer diameter of the actuating element	19 mm
type of unlocking device	key unlatching
number of switching positions	3
switch position for key distraction	0
actuating angle	
clockwise	62°
anticlockwise	62°
lock make	CES
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	plastic
material of the front ring color of the front ring	plastic black
color of the front ring	
color of the front ring Holder	black
color of the front ring Holder material of the holder	black
color of the front ring Holder material of the holder General technical data	black
color of the front ring Holder material of the holder General technical data product function	black Plastic
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function	black Plastic No
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function	black Plastic No No
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP	black Plastic No No IP65
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum	black Plastic No No IP65 1 000 1/h
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical	black Plastic No No IP65 1 000 1/h 300 000
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2	black Plastic No No IP65 1 000 1/h 300 000 S
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date)	black Plastic No No IP65 1 000 1/h 300 000 S
color of the front ring Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals	black Plastic No No IP65 1 000 1/h 300 000 S 07/01/2006

	Declaration of comornity	rest Gentificates		
General Product Approval	Declaration of Conformity	Test Certificates		
Approvals Certificates				
installation depth	50 mm			
installation width	19 mm			
mounting height	20 mm			
mounting diameter	16 mm			
shape of the installation opening	round			
fastening method	front plate mounting			
nstallation/ mounting/ dimensions				
environmental category during operation according to IEC 60721	3K6			
during storage	-40 +80 °C			
 during operation 	-25 +70 °C			







ate

Test Certificates	other

Miscellaneous

Type Test Certificates/Test Report

Confirmation

EHL

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2000-4PA01

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2000-4PA01

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2000-4PA01

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2000-4PA01&lang=en

last modified:

1/26/2022 🖸