SIEMENS

Data sheet

3SB2000-4PC01

	keyswitch, 16 mm, round, plastic, Siemens, 3 switch positions I-O-II, latching,
and use brand meno	actuating angle 2 x 62 degrees key removal I
product brand name	SIRIUS
product designation	Key-operated switches
design of the product	Single device round
product type designation	3SB2
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Key-operated switch
principle of operation of the actuating element	latching
product extension optional light source	No
material of the actuating element	plastic
outer diameter of the actuating element	19 mm
type of unlocking device	key unlatching
number of switching positions	3
switch position for key distraction	I
actuating angle	
clockwise	62°
anticlockwise	62°
lock make	CES
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	plastic
color of the front ring	black
Holder	
	Disstis
material of the holder	Plastic
material of the holder General technical data	Plastic
General technical data	Plastic
General technical data product function	
General technical data product function • EMERGENCY OFF function	No
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function	No
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP	No No IP65
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum	No No IP65 1 000 1/h
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical	No No IP65 1 000 1/h 300 000
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2	No No IP65 1 000 1/h 300 000 S
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date)	No No IP65 1 000 1/h 300 000
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals	No No IP65 1 000 1/h 300 000 S 07/01/2006
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date)	No No IP65 1 000 1/h 300 000 S
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions	No No IP65 1 000 1/h 300 000 S 07/01/2006
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature	No No IP65 1 000 1/h 300 000 S 07/01/2006
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC	No No IP65 1 000 1/h 300 000 S 07/01/2006
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting round
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting round 16 mm
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting round 16 mm 20 mm
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting height installation width	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting round 16 mm 20 mm 19 mm
General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height	No No IP65 1 000 1/h 300 000 S 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting round 16 mm 20 mm



Further information

Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2000-4PC01 Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2000-4PC01 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2000-4PC01

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2000-4PC01&lang=en

last modified:

1/26/2022 🖸