SIEMENS

Data sheet 3SB2001-6BF06

Indicator light, 16 mm, round, plastic, blue, with concentric rings



Figure similar

product brain amme SIRIUS product designation Indicator lights design of the product product type designation 33B2 Enclosure number of command points 0 Actuator design of the actuating element indicator light product extension optional light source No color of the actuating element blue product extension optional light source No color of the actuating element blue shape of the actuating element plastic shape of the actuating element yes shape of the shall yes shape of the installation opening yes shape of the actuating element yes shape of the installation opening yes		
design of the product product type designation 3SB2 Enclosure number of command points 0 Actuator design of the actuating element product extension optional light source color of the actuating element material of the actuating element plastic shape of the actuating element context diameter of the actuating element plastic shape of the actuating element plastic outer diameter of the actuating element type of unlocking device without number of switching positions Front ring product component front ring No Holder material of the holder Plastic Ceneral technical data Product function EMERGENCY OFF function EMERGENCY STOP function EMERGENCY STOP function One protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Torminals tightening torque of the screws in the bracket Ambient conditions ambient conditions ambient conditions ambient emperature Od ving storage Adv. +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method finet plate mounting fastening method finet plate mounting fastening method finet plate mounting frounting diameter 16 mm	product brand name	SIRIUS
product type designation 3SB2 Enclosure number of command points 0 Actuator design of the actuating element indicator light product extension optional light source No color of the actuating element blue material of the actuating element plastic shape of the actuating element plastic pouter diameter of the actuating element plastic pouter diameter of the actuating element plastic pouter diameter of the actuating element plastic	product designation	Indicator lights
Enclosure number of command points design of the actuating element indicator light product extension optional light source No color of the actuating element blue material of the actuating element plastic shape of the actuating element 19 plastic shape of the actuating element 19 plastic shape of the actuating element 19 pmm type of unlocking device without 19 mm type of unlocking device without 19 mm type of unlocking device 19 without 19 pmm type of unlocking device 19 product component front ring 10 No Holder 19 product tunction 19 No Holder 20 product tunction 19 pms 19 p	design of the product	Single device round
number of command points 0 Actuator design of the actuating element indicator light product extension optional light source No color of the actuating element blue material of the actuating element plastic shape of the actuating element 19 plastic shape of the actuating element 20 concentric rings outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 0 Front ring product component front ring No Holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY OFF function No • EMERGENCY STOP function No • EMERGENCY STOP function No Protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 Nm Ambient conditions ambient temperature • during operation - 25 +70 °C • during storage + 40 +80 °C • environmental category during operation according to IEC 8134ton product mounting dimensions fastening menture for first plate mounting shape of the installation opening round mounting diameter 16 mm	product type designation	3SB2
Actuator design of the actuating element indicator light product extension optional light source No Color of the actuating element blue blue material of the actuating element plastic Shape of the actuating element plastic Concentric rings Outer diameter of the actuating element 19 mm type of unlocking device without vitype of unlocking device without vitype of unlocking positions 0 Plastic Concentric ring Product component front ring No Plastic Concentric ring No Plastic Concentration Plastic Concentration Plastic Plastic Concentration Plastic Pl	Enclosure	
design of the actuating element indicator light product extension optional light source No color of the actuating element blue material of the actuating element plastic shape of the actuating element Concentric rings outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 0 Front ring product component front ring No Holder Plastic General technical data product function EMERGENCY OFF function No EMERGENCY OFF function No EMERGENCY OFF function No Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature	number of command points	0
product extension optional light source blue color of the actuating element blue material of the actuating element plastic shape of the actuating element Concentric rings outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 0 Pront ring product component front ring No Mo Model of the holder Plastic General technical data Product function No EMERGENCY OFF function No EMERGENCY STOP function No EMERGENCY STOP function No Professor of the installation of the screws in the bracket Nambient conditions tughter in the product on the product on the product of the screws in the bracket O.4 N·m Ambient conditions ambient temperature during operation Stope of the installation opening fround mounting diameter 16 mm	Actuator	
color of the actuating element plastic shape of the actuating element Concentric rings outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic General technical data product function No eMERGENCY OFF function No eMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature eduring operation -25 +70 °C eduring storage -40 +80 °C Installation/ mounting/ dimensions fastening method shape of the installation opening round mounting diameter 16 mm	design of the actuating element	indicator light
material of the actuating element Concentric rings outer diameter of the actuating element 19 mm type of unlocking device without number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature • during operation -25 +70 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round	product extension optional light source	No
shape of the actuating element outer diameter of the actuating element type of unlocking device number of switching positions product component front ring product component front ring No Holder material of the holder General technical data product function EMERGENCY OFF function EMERGENCY STOP function Poetering in IP65 reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during operation during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 19 mm without No Plastic O, No Ano Ano Ano Ano Ano Ano Ano A	color of the actuating element	blue
outer diameter of the actuating element type of unlocking device number of switching positions Front ring product component front ring No Holder material of the holder General technical data Product function EMERGENCY OFF function EMERGENCY STOP function EMERGENCY STOP function Plastic Profuction class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter i without mithout mounting/ dimensions fastening method shape of the installation opening mounting diameter 16 mm	material of the actuating element	plastic
type of unlocking device without number of switching positions 0 Front ring product component front ring No Molder material of the holder Plastic General technical data product function EMERGENCY OFF function No EMERGENCY STOP function No Protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature during operation 2-25+70 °C during storage 40+80 °C environmental category during operation according to IEC 8134610/21 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	shape of the actuating element	Concentric rings
number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature • during operation -25 +70 °C environmental category during operation according to IEC 8K6 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	outer diameter of the actuating element	19 mm
Front ring product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightning torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage -40 +80 °C environmental category during operation according to IEC 8/0721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	type of unlocking device	without
product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	number of switching positions	0
material of the holder Plastic General technical data product function	Front ring	
material of the holder General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 0.4 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	product component front ring	No
product function • EMERGENCY OFF function • EMERGENCY STOP function No protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter No No No No No No No O7/01/2006 O3/07/01/2006 O4/07/01/2006 O5/07/01/2006 O5/07/0	Holder	
product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP IP65 reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket • during operation • during operation • during storage • environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter No	material of the holder	Plastic
EMERGENCY OFF function EMERGENCY STOP function No protection class IP IP65 reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter No	General technical data	
EMERGENCY STOP function protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during storage during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 16 mm	product function	
protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) O7/01/2006 Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter IP65 P 07/01/2006 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 60721 front plate mounting front plate mounting round mounting diameter	 EMERGENCY OFF function 	No
reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter P 07/01/2006 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting front plate mounting round mounting diameter	 EMERGENCY STOP function 	No
Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting front plate mounting round	protection class IP	IP65
tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • nenvironmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting front plate mounting round	reference code according to IEC 81346-2	Р
tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage • renvironmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 0.4 N·m -25 +70 °C -40 +80 °C 3K6 front plate mounting front plate mounting round mounting diameter	Substance Prohibitance (Date)	07/01/2006
Ambient conditions ambient temperature • during operation • during storage • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening mounting diameter 16 mm	Connections/ Terminals	
ambient temperature	tightening torque of the screws in the bracket	0.4 N·m
 during operation during storage the storage the storage operation according to IEC of the storage of the installation opening operation opening operation according to IEC of the storage of the installation opening open	Ambient conditions	
● during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	ambient temperature	
environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	during operation	-25 +70 °C
Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm	during storage	-40 +80 °C
fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm		3K6
shape of the installation opening round mounting diameter 16 mm	Installation/ mounting/ dimensions	
mounting diameter 16 mm	fastening method	front plate mounting
	shape of the installation opening	round
mounting height 9 mm	mounting diameter	16 mm
· · ·	mounting height	9 mm

installation width	19 mm
installation depth	50 mm
Approvals Certificates	



General Product Approval







Declaration of Conformity



Type Test Certificates/Test Report

Test Certificates

Test Certificates	other
-------------------	-------

Miscellaneous Special Test Certific-

<u>ate</u>

Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2001-6BF06

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2001-6BF06

 $Service \& Support\ (Manuals,\ Certificates,\ Characteristics,\ FAQs,...)$

https://support.industry.siemens.com/cs/ww/en/ps/3SB2001-6BF06

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2001-6BF06&lang=en

last madified.	4/00/0000	7
last modified:	1/26/2022	. ~ i