SIEMENS

Data sheet 3SB2204-6BC06



Indicator light, 16 mm, round, plastic, red, Lampholder W2 x 4.6 d, without lamp

product type designation design of the product product type designation 3582 Enclosure number of command points Actuator design of the actuating element indicator light product extension optional light source color of the actuating element type of unlocking device number of switching positions 2 Front ring product component front ring No Hotder material of the hotder product component front ring Hotder material of the hotder Socket design W2 x 4.8d without lamp number of lampholders 1 number of switching elements 0 Enter technical data product function positions 0 Enter technical data P	product brand name	SIRIUS
product type designation 3SB2 Enclosure number of command points 0 Actustor design of the actuating element indicator light product extension optional light source Yes color of the actuating element red material of the actuating element plastic type of unlocking device without unumber of switching positions 2 Front ring product component front ring No Holder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 0 General technical data product function No	product designation	Indicator lights
Enclosure number of command points 0 Actuator design of the actuating element indicator light product extension optional light source	design of the product	Complete unit round
number of command points 0 Actuator design of the actuating element indicator light product extension optional light source Yes color of the actuating element red material of the actuating element plastic type of unlocking device without unber of switching positions 2 Front ring volunt component front ring No	product type designation	3SB2
Actuator design of the actuating element indicator light product extension optional light source color of the actuating element red material of the actuating element plastic type of unlocking device without number of switching positions 2 Front ring product component front ring No Holder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening No • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of velocation contents type of voltage Itemselvation 1 ble terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0 All Nim	Enclosure	
design of the actuating element indicator light product extension optional light source Yes color of the actuating element red material of the actuating element plastic type of unlocking device without number of switching positions 2 Pront ring Product component front ring No	number of command points	0
product extension optional light source color of the actuating element material of the actuating element type of unlocking device number of switching positions 2 Front ring product component front ring tholder material of the holder Plastic Contact block/ lampholder socket design number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) Quality contacts No Auxillary circuit number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection lab terminals type of electrical connection lab terminals tightening torque of the screws in the bracket 0.4 N·m	Actuator	
color of the actuating element red material of the actuating element plastic type of unlocking device without number of switching positions 2 Front ring product component front ring No Holder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening No product component light source No type of voltage of the operating voltage AC/DC protection class IP IP65 Teference code according to IEC 81346-2 P Substance Prohibitance (Date) 70701/2006 operating voltage rated value 560 V Auxillary circuit number of NC contacts for auxiliary contacts 0 number of NC contacts for auxiliary contacts 0 number of CC contacts for auxiliary contacts 0 number of CC contacts for auxiliary contacts 1 type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 Nm	design of the actuating element	indicator light
material of the actuating element type of unlocking device number of switching positions 2 product component front ring product component front ring No Holder material of the holder Contact block/ lampholder socket design number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value Auxillary circuit number of NC contacts for auxillary contacts number of NC contacts for auxillary contacts number of NC contacts for auxillary contacts type of electrical connection tightening torque of the screws in the bracket 1 No N	product extension optional light source	Yes
type of unlocking device without number of switching positions 2 Front ring product component front ring No Holder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening No • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 operating voltage rated value 560 V Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 1 type of electrical connection tab terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	color of the actuating element	red
number of switching positions 2 Front ring product component front ring No Molder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening No • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	material of the actuating element	plastic
Front ring product component front ring No Holder material of the holder Contact block/ lampholder socket design number of lampholders 1 number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of NO contacts for auxiliary contacts type of electrical connection tab terminals type of electrical connection tab terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	type of unlocking device	without
product component front ring No Holder material of the holder Plastic Contact block/ lampholder socket design W2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening No • EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 Connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	number of switching positions	2
material of the holder Contact block/ lampholder socket design number of lampholders 1 number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source type of voltage of the operating voltage Preference code according to IEC 81346-2 Substance Prohibitance (Date) Operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tab terminals type of electrical connection tab terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	Front ring	
material of the holder Contact block/ lampholder socket design NW2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source type of voltage of the operating voltage AC/DC protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tab terminals type of electrical connection tab terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0 O O O O O O O O O O O O	product component front ring	No
contact block/ lampholder socket design NW2 x 4.6d without lamp number of lampholders 1 number of switching elements 0 General technical data product function • positive opening • EMERGENCY STOP function No product component light source type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 Pubstance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tab terminals type of electrical connection tightening torque of the screws in the bracket 0 0 0 0 0 0 0 0 0 0 0 0 0	Holder	
socket design	material of the holder	Plastic
number of lampholders number of switching elements 0 General technical data product function • positive opening • Double	Contact block/ lampholder	
number of switching elements General technical data product function • positive opening • Dositive opening • EMERGENCY STOP function product component light source type of voltage of the operating voltage protection class IP protection class IP IP65 reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tab terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0	socket design	W2 x 4.6d without lamp
General technical data product function • positive opening • EMERGENCY STOP function product component light source type of voltage of the operating voltage protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tightening torque of the screws in the bracket No No Auxiliary circuit 0 Connections/ Terminals tightening torque of the screws in the bracket No No No No No No No No 1065 NO NO NO NO NO NO NO O7/01/2006 O7/01/2006 O 0 O 0 O 0 O 0 O 0 O 0 O 0	number of lampholders	1
product function • positive opening • EMERGENCY STOP function product component light source type of voltage of the operating voltage AC/DC protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts type of electrical connection tab terminals tightening torque of the screws in the bracket No	number of switching elements	0
 positive opening EMERGENCY STOP function No product component light source No type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 P Substance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts to to Connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m 	General technical data	
EMERGENCY STOP function Product component light source type of voltage of the operating voltage AC/DC protection class IP IP65 reference code according to IEC 81346-2 Substance Prohibitance (Date) O7/01/2006 operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts o connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket No AC/DC NO NO NO OT/01/2006 O	product function	
product component light source type of voltage of the operating voltage protection class IP protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts o connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket	 positive opening 	No
type of voltage of the operating voltage protection class IP reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket AC/DC IP65 P IP65 P O7/01/2006 O7/01/2006 O0 O O O O O O O O O O O O	EMERGENCY STOP function	No
protection class IP reference code according to IEC 81346-2 P Substance Prohibitance (Date) operating voltage rated value Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts o connections/ Terminals type of electrical connection tightening torque of the screws in the bracket I P65 P IP65 P O7/01/2006 O7/01/2006 O O O O O O O O O O O O O	product component light source	No
reference code according to IEC 81346-2 Substance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts o connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket	type of voltage of the operating voltage	AC/DC
Substance Prohibitance (Date) operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0 7/01/2006 0 0 0 0 0 0 0 0 0 0 0 0 0 0	protection class IP	IP65
operating voltage rated value 5 60 V Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 0 number of CO contacts for auxiliary contacts 0 Connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	reference code according to IEC 81346-2	P
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 Connections/ Terminals type of electrical connection tightening torque of the screws in the bracket 0.4 N·m	Substance Prohibitance (Date)	07/01/2006
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 Connections/ Terminals type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m	operating voltage rated value	5 60 V
number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts 0 Connections/ Terminals type of electrical connection tightening torque of the screws in the bracket 0.4 N·m	Auxiliary circuit	
number of CO contacts for auxiliary contacts Connections/ Terminals type of electrical connection tightening torque of the screws in the bracket 0.4 N·m	number of NC contacts for auxiliary contacts	0
Connections/ Terminals type of electrical connection tightening torque of the screws in the bracket 0.4 N·m	number of NO contacts for auxiliary contacts	0
type of electrical connection tab terminals tightening torque of the screws in the bracket 0.4 N·m		0
tightening torque of the screws in the bracket 0.4 N·m	Connections/ Terminals	
	type of electrical connection	tab terminals
Ambient conditions		0.4 N·m
	Ambient conditions	

ambient temperature -25 ... +60 °C during operation -40 ... +80 °C • during storage environmental category during operation according to IEC 3K6 60721 Installation/ mounting/ dimensions fastening method front plate mounting shape of the installation opening round mounting diameter 16 mm 9 mm mounting height installation width 19 mm installation depth 50 mm **Approvals Certificates General Product Approval Declaration of Conformity**













Test Certificates other

<u>Miscellaneous</u>

Special Test Certificate

Type Test Certificates/Test Report Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2204-6BC06

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2204-6BC06

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2204-6BC06

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2204-6BC06&lang=en

last modified:	1/26/2022	j