SIEMENS

Data sheet 3SB2455-0B



Contact block, 1 NO, soldering pin connection

Figure similar

product brand name	SIRIUS	
product designation	contact block	
product type designation	3SB2	
Contact block/ lampholder		
number of lampholders	0	
General technical data		
product function positive opening	No	
suitability for integration	pushbutton / selector button	
type of voltage		
of the operating voltage	AC/DC	
protection class IP		
• of the enclosure	IP40	
of the terminal	IP00	
reference code according to IEC 81346-2	S	
Substance Prohibitance (Date)	07/01/2006	
operating voltage		
• at AC		
— at 50 Hz rated value	5 230 V	
— at 60 Hz rated value	5 230 V	
100 11 1	5 000 1/	
at DC rated value	5 230 V	
Auxiliary circuit	5 230 V	
	0 0	
Auxiliary circuit		
Auxiliary circuit number of NC contacts for auxiliary contacts	0	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts	0	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts	0	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12	0 1 0	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value	0 1 0 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value	0 1 0 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value	0 1 0 10 A 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value	0 1 0 10 A 10 A 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 110 V rated value	0 1 0 10 A 10 A 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value • at 230 V rated value	0 1 0 10 A 10 A 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value operational current at DC-12	0 1 0 10 A 10 A 10 A 10 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value • at 230 V rated value	0 1 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 24 V rated value • at 24 V rated value • at 24 V rated value operational current at DC-12 • at 24 V rated value • at 60 V rated value	0 1 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A 4 A	
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 24 V rated value • at 24 V rated value operational current at DC-12 • at 24 V rated value • at 60 V rated value • at 60 V rated value • at 110 V rated value • at 110 V rated value • at 110 V rated value	0 1 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A 4 A 5 A 2.5 A	
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 24 V rated value • at 24 V rated value • at 24 V rated value operational current at DC-12 • at 24 V rated value • at 60 V rated value	0 1 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A 4 A	

• at 24 V rated value	3 A	
• at 60 V rated value	1.2 A	
• at 110 V rated value	0.7 A	
• at 230 V rated value	0.3 A	
Connections/ Terminals		
type of electrical connection	solder pin connectors	
Ambient conditions		
ambient temperature		
during operation	-25 +70 °C	
during storage	-40 +80 °C	
Installation/ mounting/ dimensions		
fastening method	clip-on	
height	19 mm	
width	18 mm	
depth	29 mm	
Approvals Certificates		
General Product Approval		Declaration of Conformity







<u>KC</u>





Declaration of Conformity

other



Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-0B

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2455-0B

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2455-0B&lang=en

last modified:	12/21/2020