SIEMENS

Data sheet 3SB2455-0C



Contact block, 1 NC, soldering pin connection

Figure similar

product brand name	SIRIUS
product designation	contact block
product type designation	3SB2
Contact block/ lampholder	
number of lampholders	0
General technical data	
product function positive opening	Yes
suitability for integration	pushbutton / selector button
type of voltage	
of the operating voltage	AC/DC
protection class IP	
 of the enclosure 	IP40
of the terminal	IP00
reference code according to IEC 81346-2	S
Substance Prohibitance (Date)	07/01/2006
operating voltage	
• at AC	
— at 50 Hz rated value	5 230 V
— at 60 Hz rated value	5 230 V
at DO rate division	5 220 V
 at DC rated value 	5 230 V
at DC rated value Auxiliary circuit	5 230 V
	1
Auxiliary circuit	
Auxiliary circuit number of NC contacts for auxiliary contacts	1
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts	1 0
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts	1 0
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12	1 0 0
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value	1 0 0
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value	1 0 0 10 A 10 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value	1 0 0 10 A 10 A 10 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value	1 0 0 10 A 10 A 10 A
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15	1 0 0 10 A 10 A 10 A
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value	1 0 0 10 A 10 A 10 A 10 A
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 110 V rated value	1 0 0 10 A 10 A 10 A 10 A
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 230 V rated value	1 0 0 10 A 10 A 10 A 10 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value operational current at DC-12	1 0 0 10 A 10 A 10 A 10 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 110 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value • at 230 V rated value • at 24 V rated value operational current at DC-12 • at 24 V rated value	1 0 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts number of CO contacts for auxiliary contacts number of CO contacts for auxiliary contacts operational current at AC-12 • at 24 V rated value • at 60 V rated value • at 230 V rated value operational current at AC-15 • at 24 V rated value • at 110 V rated value • at 230 V rated value • at 230 V rated value • at 24 V rated value • at 24 V rated value • at 250 V rated value operational current at DC-12 • at 24 V rated value • at 60 V rated value	1 0 0 10 A 10 A 10 A 10 A 4 A 4 A 4 A 4 A

• at 24 V rated value	3 A		
• at 60 V rated value	1.2 A		
• at 110 V rated value	0.7 A		
• at 230 V rated value	0.3 A		
Connections/ Terminals			
type of electrical connection	solder pin connectors		
Ambient conditions			
ambient temperature			
 during operation 	-25 +70 °C		
during storage	-40 +80 °C		
Installation/ mounting/ dimensions			
fastening method	clip-on		
height	19 mm		
width	18 mm		
depth	29 mm		
Approvals Certificates			
General Product Approval		Declaration of Conformity	

<u>KC</u>

Declaration of Con-

other



formity

Confirmation

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2455-0C

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-0C

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2455-0C

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2455-0C&lang=en

last modified:	1/6/2021 🗗
last modified.	1/0/2021