## **SIEMENS**

## **Data sheet**



Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, green, 30 mm, latching, Pull-to-unlatch mechanism

product brand name product designation Mushroom pushbuttons  design of the product Actuating/signaling element  product type designation 3SU1  product line Metal, shiny, 22 mm  Enclosure number of command points 1  Actuator  design of the actuating element principle of operation of the actuating element product extension optional light source color of the actuating element material of the actuating element shape of the actuating element plastic shape of the actuating element round	
design of the product product type designation product line Metal, shiny, 22 mm  Enclosure number of command points 1  Actuator design of the actuating element principle of operation of the actuating element product extension optional light source color of the actuating element material of the actuating element plastic  Actuating element plastic	
product type designation product line  Metal, shiny, 22 mm  Enclosure number of command points  1  Actuator design of the actuating element illuminated principle of operation of the actuating element latching product extension optional light source yes color of the actuating element green material of the actuating element plastic	
product line Metal, shiny, 22 mm  Enclosure  number of command points 1  Actuator  design of the actuating element illuminated  principle of operation of the actuating element latching  product extension optional light source Yes  color of the actuating element green  material of the actuating element plastic	
Enclosure  number of command points  1  Actuator  design of the actuating element illuminated principle of operation of the actuating element latching product extension optional light source Yes color of the actuating element green material of the actuating element plastic	
number of command points  Actuator  design of the actuating element illuminated  principle of operation of the actuating element latching  product extension optional light source Yes  color of the actuating element green  material of the actuating element plastic	
Actuator  design of the actuating element illuminated  principle of operation of the actuating element latching  product extension optional light source Yes  color of the actuating element green  material of the actuating element plastic	
design of the actuating element     illuminated       principle of operation of the actuating element     latching       product extension optional light source     Yes       color of the actuating element     green       material of the actuating element     plastic	
principle of operation of the actuating element product extension optional light source color of the actuating element green material of the actuating element plastic	
product extension optional light source  color of the actuating element  material of the actuating element  plastic	
color of the actuating element green  material of the actuating element plastic	
material of the actuating element plastic	
shape of the actuating element	
Shape of the actuality element	
outer diameter of the actuating element 30 mm	
type of unlocking device pull-to-unlatch mechanism	
number of switching positions 2	
Front ring	
product component front ring Yes	
design of the front ring Standard	
material of the front ring  Metal, high gloss	
color of the front ring silver	
General technical data	
product function	
EMERGENCY OFF function     No	
EMERGENCY STOP function     No	
protection class IP IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance	
• according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms	
vibration resistance	
• according to IEC 60068-2-6 10 500 Hz: 5g	
operating frequency maximum 1 800 1/h	
mechanical service life (operating cycles) typical 500 000	
reference code according to IEC 81346-2	
Substance Prohibitance (Date) 10/01/2014	
Ambient conditions	
ambient temperature	
• during operation -25 +70 °C	
• during storage -40 +80 °C	

environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)	
Installation/ mounting/ dimensions		
height	30 mm	
width	30 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	27.5 mm	
installation width	30 mm	
installation depth	24.4 mm	
Approvals Certificates		

**General Product Approval** 

**Declaration of Conformity** 



Confirmation









**Test Certificates** 

Marine / Shipping

Type Test Certificates/Test Report

Special Test Certific-<u>ate</u>









other **Environment** 

> Confirmation **Environmental Con-**

**firmations** 

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-1AA40-0AA0


Cax online generator


http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1051-1AA40-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-1AA40-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1051-1AA40-0AA0&lang=en





last modified: 1/27/2022 🖸