

accessory: adapter cable for RFID safety switch 3SE63, for connection to, for example, SIMATIC ET200eco PN-F or ET 200AL-F M12 socket 8-pole at one end, M12 plug 5-pole at the other end. Cable 500 mm long.



General technical data	
operational current at 40 °C rated value	2 A
operating voltage rated value	30 V
ambient temperature during operation	-25 ... +85 °C
overvoltage category	2
degree of pollution	3
protection class IP	IP68

Certificates/ approvals		
General Product Approval	Declaration of Conformity	other

[Confirmation](#)



[Confirmation](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SX5601-3SV00-1AK3>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SX5601-3SV00-1AK3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SX5601-3SV00-1AK3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SX5601-3SV00-1AK3&lang=en



A		B
1	→	1
2	→	1
3	→	3
4	→	4
5	→	n.c.
6	→	1
7	→	2
8	→	5

