

Connecting cable 1 m, for connection of position switch 3SE52*-1AE2 and 3SE51*1AE3, M12 connector 5-pole as well as emergency stop enclosure 3SU1 with M12 connector 5-pole to e.g. SIMATIC. M12 socket 5-pole at one end and M12 plug 5-pole at the other end.



General technical data	
operational current at 40 °C rated value	4 A
operating voltage rated value	125 V
number of poles	5
wire length of connection cable	1 m
ambient temperature during operation	-25 ... +80 °C
connector coding of the M12 circular connector	A - Standard
type of electrical connection	connector M12
degree of pollution	3
protection class IP	IP67
material	
• of contact main body	PUR

Certificates/ approvals	
General Product Approval	other
Confirmation	Confirmation

Further information

Siemens has decided to exit the Russian market (see here).
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.
 Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SX5601-3SV15>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SX5601-3SV15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3SX5601-3SV15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SX5601-3SV15&lang=en

last modified: 7/8/2021