

Filterless enclosure cooling unit KG 4274-230V



Product Features


Brand Name:	SoliTherm SlimLine
Order Number:	42740001
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 54
Optional:	In stainless steel order no. 4274002
Approvals:	CE, cURus, cULus
UL File Nummer:	cURus (SA32278), cULus (E498756)
Accessories:	NEMA 4X cover
Taric Code:	84158200

Technical data KG 4274-230V

Cooling capacity L35L35:	1.5 kW @ 50 Hz 1.5 kW @ 60 Hz
Cooling capacity L35L50:	1.2 kW
Compressor:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	530 g / 19 oz
High / low pressure:	37 / 9.6 bar 536 / 140 psig
Temperature range:	+10°C - +55°C
Air volume flow (system / unimpeded):	Ambient air circuit: 430 / 1200 m ³ /h Cabinet air circuit: 200 / 850 m ³ /h
Mounting:	External / Recessed
Dimension H x W x D:	1,550 x 395 x 145 mm
Weight:	50 kg
Cut out dimensions:	1,531 x 376 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	4.3 A @ 50 Hz 5.5 A @ 60 Hz
Starting current:	22 A
Max. current:	7 A
Nominal power L35L35:	1.00 kW @ 50 Hz 1.23 kW @ 60 Hz
Max. power:	1.58 kW
Fuse:	10 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview product group Cabinet cooling units - SlimLine](#)

Performance Graph:




click image to enlarge

Air flow:



click image to enlarge

Cut out dimensions:



click image to enlarge