



Klemsan®

600104 CT3-AC-LP

True RMS Current Transducer

General		
	Casing Width (mm)	36
	Connections	Screw terminal
Configurable Voltage Range		
	0-24VAC	--
	0-36VAC	--
	0-54VAC	--
	0-80VAC	--
	0-120VAC	--
	0-170VAC	--
	0-250VAC	--
	0-400VAC	--
	0-450VAC	--
	0-500VAC	--
	0-24VDC	--
	0-54VDC	--
	0-120VDC	--
	0-250VDC	--
	0-450VDC	--
Configurable Current Range		
	0-1AAC	✓
	0-2AAC	✓
	0-3AAC	✓
	0-4AAC	✓
	0-5AAC	✓

Input Signal	Frequency	40-70 Hz
	Surge Overload	20xin (100 A) for 1 sec.
	Constant Overload	10A (2x Rated IN)
	Input Impedances	49.9 Ω (burden resistor)
Type	0-20mA	—
	4-20mA	✓
	\pm 20mA	—
	20-0mA	—
	20-4mA	—
	0-5V	—
	0-10V	—
	\pm 5V	—
	\pm 10V	—
	10-0V	—
Analog Output	Max. Current	24 mA
	Max. Voltage	—
	Max. Load	10 Ω (for voltage) / 600 Ω (for current)
Voltage	AC	—
	DC	9-30V
Supply	Frequency	—
Power Consumption	DC	<1.5W
	AC	<4VA
General	Isolation	1.5 kVrms, 2-way
	Test Voltage between Input-Output	4 kV during 1 min.
	Linearity	<0.2%
	Response Time	350ms
	Ripple	<80mV
	Accuracy	<0.2% (full scale, 25°C)
	Temperature Coefficient	150 ppm/°C
Ambient Conditions	Operating Temperature	-20°C +60°C

	Storing Temperature	-40°C +75°C
	Relative Humidity (No Condensation)	Maks. 95%
General	Protection Class	IP20
	Mounting Type	Panel or Rail
EMC-EMI	Radiated Emissionas Test, 61000-6-2/AC:2012, 61000-6-4:2007/A1:2011	✓
General	Packing Unit	1
	Dimensions	
	Weight (g)	71

Avrupa standartlarına uygunluk belgesi - CE Certificate

© 2020 Klemsan A.Ş.
www.klemsan.com