



Klemsan®

601401 ETOR-2

Ethernet Gateway (TCP/IP - RS232)

| General | | |
|------------------------------|-----------------------------|--|
| | Casing Width (mm) | 17,5 |
| | Connections | Screw Terminal (for supply and serial interface) |
| | Working Mode | Server or Client Selectable (bidirectional) |
| | Configuration | Mini USB Port or Web Interface |
| | DHCP (Automatic IP Receive) | ✓ |
| | ARP | ✓ |
| | Ping Blocking | ✓ |
| | LED Indicators | ✓ |
| | Reset Function | ✓ |
| | ESD Protection | ✓ |
| | Driver Supported | Windows XP/Vista/7/8/8.1 |
| Ethernet Interface | | |
| | Number of Ports | 1 |
| | Operation Modes | Modbus TCP, Modbus RTU over TCP, Modbus ASCII over TCP |
| Number of Remote Connections | | |
| | Server Mode | 6 |
| | Client Mode | 1 |
| Ethernet Interface | | |
| | Connector | RJ45 |
| | Data Transmission Rate | 10/100 Base-TX |
| Serial Interface | | |
| | Number of Ports | 1 |
| | Operation Modes | Modbus RTU, Modbus ASCII |
| | Serial Standart | RS232 |
| Number of Serial Devices | | |
| | Server Mode | 1 |
| | Client Mode | 1 |

| | | |
|--|-------------------------------------|-------------------|
| Serial Communication Parameters | Baud Rate | 300 to 115200 bps |
| | Data Bit | 8 |
| | Stop Bits | 1 or 2 |
| | Parity | None, Even, Odd |
| Voltage | AC | 18-50V |
| | DC | 18-50V |
| Consumption | AC | <2.2VA |
| | DC | <1.2W |
| Supply | Frequency | 45-65Hz |
| Galvanic Isolation | Supply - Ethernet Port | 1500VRMS, 2250VDC |
| | Supply - Serial Port | 1500VRMS, 2250VDC |
| | Serial Port - Ethernet Port | 2500VRMS |
| Mechanical Properties | Weight (g) | 58 |
| | Packing Unit | 1 |
| | Protection Class | IP20 |
| | Assembly Type | Rail Mount |
| Ambient Conditions | Operating Temperature | -10°C +60°C |
| | Storing Temperature | -30°C +80°C |
| | Relative Humidity (No Condensation) | Maks. 95% |
| EMC-EMI | TS EN 55022, TS EN 55024 | |
| General | Schematics | |
| | Dimensions | |

Avrupa standartlarına uygunluk belgesi - CE Certificate

ETOR Setup

ETOR User Guide

**Order
Info**

601401 Ethernet Gateway (TCP/IP - RS232)

