



Klemmsan®

601440 GTOR

GPRS Gateway

General Product Information	Width	17,5 mm
	Connections	Screw Terminal
	Mount Type	Rail Mount
	Configuration	Configuration through USB Micro USB connection interface
	IP-Based Security	✓
	LED Displays	✓
	Reset Function	✓
	ESD Protection	✓
	Drivers	WindowsXP/Vista/7/8/10
GPRS Interface	SIM/USIM	3V/1.8V
	Quad Band	850/900/1800/1900MHz
GPRS Multi Slot Class	Downlink	Class 12 85.6kbps
	Uplink	Class 12 85.6kbps
GPRS Interface	GPRS Mobile Station	Class B
	Compliant to GSM Phase 2/2+	Class 4 (2W @850/900MHz) Class 1 (1W @1800/1900MHz)
Serial Interface	Number of Ports	1
	Serial Connection Standard	RS485
Number of Serial Connection Devices	Server Mode	64
	Receiver Mode	(-)
Serial Link Parameters	Baud Value	300 - 115200 bps
	Data Bit	8
	Stop Bit	1 or 2
	Parity	—, Double, Single

Protocols		MODBUS TCP; MODBUS RTU over TCP; MODBUS ACII over TCP
Supply Voltage	DC	11-30VDC
	AC	—
isolation		1.5kV RMS
Relative Humidity		%95 non-condensing
Operating Frequency		45-65Hz
Protection Class		IP20
Power consumption	DC	1.2W
	AC	—
Mechanical Properties	Weight (g)	
	Packing Unit	1
	—	1

Avrupa standartlarına uygunluk belgesi - CE Certificate

GTOR Setup

GTOR User Guide

Order Info

601440 GPRS Gateway