



# Klemsan®

## 602400 Ascon 352

Signal-Temperature Transducer

<b>General</b>		
	Casing Width (mm)	17,5
	Connections	Screw terminal
<b>Input</b>	Sensor Type	mV,V, mA - PT100(2,3,4wire) - Thermocouple(J,K,E,R,S)
	Connection Method	2 wire or 3 wire or 4 wire
	Temperature Measuring Range	-150°C +800°C Configurable
	Sensor Excitation Current	<0.5mA
<b>Output</b>	Output Signal	RS485
	Linear Output Range	3.6mA - 23.6mA
	Max. Load	—
	Ripple	—
<b>Voltage</b>	AC	—
	DC	11-30V
<b>General</b>	Isolation	3 way - 1,5 kV RMS
	Measurement Error	< 0.1% (Full Scale)
	Temperature Coefficient	≤ 0.02%/°C
	Response Time	< 10ms
	Sensor Failure Indication	Voltage output mode: short circuit
<b>Ambient Conditions</b>	Operating Temperature	-20°C +60°C
	Storing Temperature	-40°C +75°C
	Relative Humidity (No Condensation)	Maks. 95%
<b>General</b>	Protection Class	IP20
	Mounting Type	Rail Mounted

<b>EMC-EMI</b>	Radiated Emissions Test, 61000-6-2/AC:2012, 61000-6-4:2007/A1:2011	Any
<b>General</b>	Packing Unit	1
	Dimensional Drawings	—
	Weight (g)	42

Avrupa standartlarına uygunluk belgesi - CE Certificate

**Order Info**

602400 Signal-Temperature Transducer

© 2020 Klemsan A.Ş.  
www.klemsan.com