



Figure similar

SIPLUS S7-300 SM 322 (-1BF01) based on 6ES7322-1BF01-0AA0 with conformal coating, -25...+70 °C, digital output SM 322, isolated, 8 DQ, 24 V DC, 2 A, 1x 20-pole

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	60 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	6.8 W
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes; Electronic
• Response threshold, typ.	3 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	10 W
Load resistance range	
• lower limit	12 Ω
• upper limit	4 kΩ
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	2 A
• for signal "1" permissible range for 0 to 40 °C, min.	5 mA
• for signal "1" permissible range for 0 to 40 °C, max.	2.4 A
• for signal "1" permissible range for 40 to 60 °C, min.	5 mA
• for signal "1" permissible range for 40 to 60 °C, max.	2.4 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	100 μs
• "1" to "0", max.	500 μs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes

Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. 	100 Hz
<ul style="list-style-type: none"> • with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> • with inductive load (acc. to IEC 60947-5-1, DC13), max. 	0.5 Hz
<ul style="list-style-type: none"> • on lamp load, max. 	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 60 °C, max.	4 A
— up to 70 °C, max.	4 A
vertical installation	
— up to 40 °C, max.	4 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	No
Diagnoses	
<ul style="list-style-type: none"> • Wire-break 	No
<ul style="list-style-type: none"> • Short-circuit 	No
<ul style="list-style-type: none"> • Fuse blown 	No
<ul style="list-style-type: none"> • missing load voltage 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Rated load voltage PWR (green) 	No
<ul style="list-style-type: none"> • Fuse OK FSG (green) 	No
<ul style="list-style-type: none"> • Status indicator digital output (green) 	Yes; per channel
Potential separation	
Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels 	Yes
<ul style="list-style-type: none"> • between the channels, in groups of 	4
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes; Optocoupler
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
Railway application	
<ul style="list-style-type: none"> • EN 50121-4 	No
<ul style="list-style-type: none"> • EN 50155 	No
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	-25 °C
<ul style="list-style-type: none"> • max. 	70 °C; = Tmax; 60 °C @ UL/cUL use
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. 	-40 °C
<ul style="list-style-type: none"> • max. 	70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	5 000 m
<ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude 	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request

— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
connection method / header	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	190 g
last modified:	1/16/2021 