



Figure similar

SIPLUS S7-300 SM 322-40-pole based on 6ES7322-1HF10-0AA0 with conformal coating, -25...+60 °C, digital output isolated 8 DQ (relay), 1x 40-pole, 24 V DC, 5 A or 230 V AC, 5 A, plugs with spring-loaded terminal can be used from 6ES7392-1BM01-0AA0

Supply voltage	
Load voltage L+	
• Rated value (DC)	120 V
Load voltage L1	
• Rated value (AC)	230 V
Input current	
from supply voltage L+, max.	125 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	4.2 W
Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No; to be provided externally
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	1 500 W; 230 V AC
• Low energy/fluorescent lamps with electronic control gear	10x 58 W
• Fluorescent tubes, conventionally compensated	1x 58 W
• Fluorescent tubes, uncompensated	10x 58 W
Output current	
• for signal "1" rated value	5 A
• for signal "1" minimum load current	5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz
• With inductive load (to IEC 60947-5-1, DC13/AC15), max.	0.5 Hz
• on lamp load, max.	2 Hz
• mechanical, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 60 °C, max.	5 A
— up to 70 °C, max.	5 A
vertical installation	
— up to 40 °C, max.	5 A

Relay outputs	
<ul style="list-style-type: none"> Rated supply voltage of relay coil L+ (DC) Contact connection (internal) Number of operating cycles, max. 	24 V No 300 000; 300 000 (24 V DC, at 2 A); 200 000 (120 V AC, at 3 A); 100 000 (230 V AC, at 3 A)
Switching capacity of contacts	
<ul style="list-style-type: none"> with inductive load, max. with resistive load, max. Thermal continuous current, max. 	3 A; 3 A (230 V DC), 2 A (24 V AC) 8 A; 8 A (230 V DC), 5 A (24 V AC) 8 A
Cable length	
<ul style="list-style-type: none"> shielded, max. unshielded, max. 	1 000 m 600 m
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	No
Diagnoses	
<ul style="list-style-type: none"> Wire-break Short-circuit Fuse blown missing load voltage 	No No No No
Diagnostics indication LED	
<ul style="list-style-type: none"> Rated load voltage PWR (green) Fuse OK FSG (green) Status indicator digital output (green) 	No No Yes
Potential separation	
Potential separation digital outputs	
<ul style="list-style-type: none"> between the channels between the channels, in groups of between the channels and backplane bus 	Yes 1 Yes; Optocoupler
Isolation	
Isolation tested with	2 000 V AC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
<ul style="list-style-type: none"> EN 50155 	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007 (see SIOS entry 109755985)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	-25 °C; = Tmin 60 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. Ambient air temperature-barometric pressure-altitude 	2 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
<ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
<ul style="list-style-type: none"> to biologically active substances according to EN 60721-3-3 to chemically active substances according to 	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52

EN 60721-3-3 — to mechanically active substances according to EN 60721-3-3	(severity degree 3); * Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
connection method / header	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	320 g
last modified:	1/16/2021 