



Figure similar

SIPLUS S7-300 SM 326 10F-DQ based on 6ES7326-2BF10-0AB0 with conformal coating, -25...+60 °C, 70° with forced convection, digital output 24 V DC/2A PP, fail-safe digital output for SIMATIC S7F systems, with diagnostic alarm, LVV, 1x 40-pole

Supply voltage	
Rated value (DC)	24 V; 1L+
Reverse polarity protection	Yes
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; 2L+, 3L+
<ul style="list-style-type: none"> Reverse polarity protection 	No
Input current	
from supply voltage 1L+, max.	100 mA
from load voltage 2L+ (without load), max.	100 mA
from load voltage 3L+ (without load), max.	100 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	6 W
Digital outputs	
Number of digital outputs	10
Short-circuit protection	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> on lamp load, max. 	5 W
Output current	
<ul style="list-style-type: none"> for signal "1" rated value 	2 A
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 40 °C, min. 	7 mA
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 40 °C, max. 	2.4 A
<ul style="list-style-type: none"> for signal "1" permissible range for 40 to 60 °C, min. 	7 mA
<ul style="list-style-type: none"> for signal "1" permissible range for 40 to 60 °C, max. 	2.4 A
<ul style="list-style-type: none"> for signal "0" residual current, max. 	0.5 mA
Switching frequency	
<ul style="list-style-type: none"> with resistive load, max. 	25 Hz
<ul style="list-style-type: none"> with inductive load, max. 	25 Hz
<ul style="list-style-type: none"> on lamp load, max. 	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	10 A
— up to 60 °C, max.	6 A
vertical installation	
— up to 40 °C, max.	5 A
Cable length	
<ul style="list-style-type: none"> shielded, max. 	1 000 m

• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Yes
• between the channels, in groups of	5
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	370V for 1 min
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Highest safety class achievable in safety mode	
• acc. to EN 954	Cat. 4
• Performance level according to ISO 13849-1	e
• SIL acc. to IEC 61508	SIL 3
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	60 °C; = T max; *+70 °C when forced convection at a minimum air speed of 0.3 m/s through the modules is ensured. If in the course of maintenance or automatic diagnosis it is determined that the admissible specified parameters have been exceeded, the modules should be subjected to a proof test (function check) by the manufacturer.
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible);

71.04	level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
connection method / header	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	330 g
last modified:	1/16/2021 