



Figure similar

SIPLUS S7-1500 PM 1507 24V/3A

SIPLUS S7-1500 PM 1507 24 V/3 A -40 ... +70°C with conformal coating based on 6EP1332-4BA00 . STABILIZED POWER SUPPLY INPUT: 120/230 V AC OUTPUT: 24 V/3 A DC

Input	
Input	1-phase AC
• Note	Automatic range selection
supply voltage	
• 1 at AC rated value	120 V
• 2 at AC rated value	230 V
input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × V <sub>in</sub> rated, 1.3 ms
Mains buffering	at V <sub>in</sub> = 93/187 V
Mains buffering at I <sub>out</sub> rated, min.	20 ms; at V <sub>in</sub> = 93/187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	45 ... 65 Hz
input current	
• at rated input voltage 120 V	1.4 A
• at rated input voltage 230 V	0.8 A
Switch-on current limiting (+25 °C), max.	23 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I <sup>2</sup> t, max.	1.3 A <sup>2</sup> ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: 10 A characteristic B or 6 A characteristic C
Output	
Output	Controlled, isolated DC voltage
Rated voltage V <sub>out</sub> DC	24 V
• output voltage at output 1 at DC rated value	24 V
Total tolerance, static ±	1 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
product function output voltage adjustable	No
Status display	LED green for 24 V OK; LED red for error; LED yellow for stand-by
On/off behavior	No overshoot of V <sub>out</sub> (soft start)

Startup delay, max.	1.5 s
Voltage rise, typ.	10 ms
Rated current value I <sub>out</sub> rated	3 A
Current range	0 ... 3 A
supplied active power typical	72 W
short-term overload current	
• on short-circuiting during the start-up typical	12 A
• at short-circuit during operation typical	12 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	70 ms
• at short-circuit during operation	70 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
<b>Efficiency</b>	
Efficiency at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	87 %
Power loss at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	11 W
<b>Closed-loop control</b>	
Dynamic mains compensation (V <sub>in</sub> rated ±15 %), max.	0.1 %
Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> ± typ.	1 %
Dynamic load smoothing (I <sub>out</sub> : 10/90/10 %), U <sub>out</sub> ± typ.	3 %
Load step setting time 10 to 90%, typ.	5 ms
Load step setting time 90 to 10%, typ.	5 ms
setting time maximum	5 ms
<b>Protection and monitoring</b>	
Output overvoltage protection	Additional control loop, limitation (closed loop control) at < 28.8 V
Current limitation	3.15 ... 3.6 A
Current limitation, typ.	3.4 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Overload/short-circuit indicator	-
<b>Safety</b>	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178 and EN 61131-2
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.4 mA
Degree of protection (EN 60529)	IP20
<b>Approvals</b>	
CE mark	Yes
<b>EMC</b>	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature in horizontal mounting position during operation	-40 ... +70; with natural convection
ambient temperature during storage and transport	-40 ... +85
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation acc. to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity acc.	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52

to EN 60721-3-3	(severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust
coating for equipped printed circuit board acc. to EN 61086	Yes; Class 2 for high availability
type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating acc. to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal Coating, Class A
<b>Mechanics</b>	
Connection technology	Screw-/spring clamp connection
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup>
• Output	L+, M: 2 spring-loaded terminals each for 0.5 to 2.5 mm <sup>2</sup>
product function	
• removable terminal at input	Yes
• removable terminal at output	Yes
width of the enclosure	50 mm
height of the enclosure	147 mm
depth of the enclosure	129 mm
required spacing	
• top	40 mm
• bottom	40 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.45 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Can be mounted onto S7-1500 rail
MTBF at 40 °C	1 611 993 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

