

product type designation



SIPLUS NET CP343-1 LEAN

SIPLUS NET CP 343-1 Lean based on 6GK7343-1CX10-0XE0 with conformal coating, -25...+60 °C, communications processor for connection of SIMATIC S7-300 to Industrial Ethernet via TCP/IP and UDP, multicast, send/receive with and without RFC1006, fetch/ write, S7 communication (server) PROFINET IO device integrated 2-port switch ERTEC 200, module replacement without PG, SNMP diagnostics, initialization via LAN,

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet for power supply 	2 1
type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface at the 1st interface / acc. to Industrial Ethernet 	RJ45 port RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> for power supply 	2-pole plugable terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	24 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical from external supply voltage / at DC / at 24 V / typical from external supply voltage / at DC / at 24 V / maximum 	0.2 A 0.16 A 0.2 A
power loss [W]	5.8 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation for horizontally arranged busbars / during operation during storage during transport 	-25 ... +40 °C -25 ... +60 °C -40 ... +70 °C -40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	

<ul style="list-style-type: none"> with condensation / acc. to IEC 60068-2-38 / maximum 	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances <ul style="list-style-type: none"> conformity acc. to EN 60721-3-3 	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
<ul style="list-style-type: none"> conformity acc. to EN 60721-3-6 	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances <ul style="list-style-type: none"> conformity acc. to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
<ul style="list-style-type: none"> conformity acc. to EN 60721-3-6 	Yes
resistance to mechanically active substances <ul style="list-style-type: none"> conformity acc. to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
<ul style="list-style-type: none"> conformity acc. to EN 60721-3-6 	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / acc. to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.22 kg
fastening method <ul style="list-style-type: none"> S7-300 rail mounting 	Yes
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	8
data volume <ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
number of Multicast stations	8
performance data / S7 communication	
number of possible connections / for S7 communication <ul style="list-style-type: none"> maximum 	4
service <ul style="list-style-type: none"> of SIMATIC communication / as server 	Yes
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	12
performance data / PROFINET communication / as PN IO controller	
product function / PROFINET IO controller	No
performance data / PROFINET communication / as PN IO device	
product function / PROFINET IO device	Yes
data volume <ul style="list-style-type: none"> as user data for input variables / as PROFINET IO device / maximum 	512 byte
<ul style="list-style-type: none"> as user data for output variables / as PROFINET IO 	512 byte

device / maximum	
<ul style="list-style-type: none"> • as user data for input variables / for each sub-module as PROFINET IO device 	240 byte
<ul style="list-style-type: none"> • as user data for output variables / for each sub-module as PROFINET IO device 	240 byte
<ul style="list-style-type: none"> • as user data for the consistency area for each sub-module 	240 byte
number of submodules / per PROFINET IO-Device	32
performance data / telecontrol	
protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.4 or higher / STEP 7 Professional V11 (TIA Portal) or higher
identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> • I&M1 – higher level designation/location designation 	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes
product function	
<ul style="list-style-type: none"> • switch-managed 	No
<ul style="list-style-type: none"> • with IRT / PROFINET IO switch 	No
<ul style="list-style-type: none"> • configuration with STEP 7 	Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> • ring redundancy 	Yes
<ul style="list-style-type: none"> • redundancy manager 	No
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product functions / security	
product function	
<ul style="list-style-type: none"> • password protection for Web applications 	No
<ul style="list-style-type: none"> • ACL - IP-based 	Yes
<ul style="list-style-type: none"> • ACL - IP-based for PLC/routing 	No
<ul style="list-style-type: none"> • switch-off of non-required services 	Yes
<ul style="list-style-type: none"> • blocking of communication via physical ports 	Yes
<ul style="list-style-type: none"> • log file for unauthorized access 	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security

functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

8/3/2021 