



Figure similar

SIMATIC ET 200SP, TM Posinput 1 counter and position decoder module for RS-422 incremental encoder or SSI absolute encoder, 2 DI, 2 DQ suitable for BU type A0, pack quantity: 1 unit

General information	
Product type designation	TM PosInput 1
Firmware version	V2.0
<ul style="list-style-type: none"> FW update possible 	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	STEP 7 V16 or higher
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.6 (use previous version *6BA00*)
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	GSD Revision 5
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	GSDML V2.34
Supply voltage	
Rated value (DC)	24 V
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> permissible range, lower limit (DC) 	19.2 V
<ul style="list-style-type: none"> permissible range, upper limit (DC) 	28.8 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
Current consumption, max.	75 mA; without load
Encoder supply	
Number of outputs	2
5 V encoder supply	
<ul style="list-style-type: none"> 5 V 	Yes
<ul style="list-style-type: none"> Short-circuit protection 	Yes; electronic/thermal
<ul style="list-style-type: none"> Output current, max. 	300 mA; Total current of all encoders
24 V encoder supply	
<ul style="list-style-type: none"> 24 V 	Yes; L+ (-0.8 V)
<ul style="list-style-type: none"> Short-circuit protection 	Yes; electronic/thermal
<ul style="list-style-type: none"> Output current, max. 	300 mA; Total current of all encoders
Power loss	
Power loss, typ.	1.5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Inputs 	16 byte; 4 bytes in Fast mode
<ul style="list-style-type: none"> Outputs 	12 byte; 4 bytes for Motion Control, 0 bytes for Fast mode

Hardware configuration	
Automatic encoding	Yes
• Mechanical coding element	Yes
• Type of mechanical coding element	type B
Digital inputs	
Number of digital inputs	2
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
• Gate start/stop	Yes; only for pulse and incremental encoders
• Capture	Yes
• Synchronization	Yes; only for pulse and incremental encoders
• Freely usable digital input	Yes
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-5 ... +5 V
• for signal "1"	+11 to +30V
• permissible voltage at input, min.	-30 V; -5 V continuous, -30 V brief reverse polarity protection
• permissible voltage at input, max.	30 V
Input current	
• for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	6 µs; for parameterization "none"
— at "1" to "0", min.	6 µs; for parameterization "none"
for technological functions	
— parameterizable	Yes
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	2
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
Digital output functions, parameterizable	
• Switching tripped by comparison values	Yes
• Freely usable digital output	Yes
Switching capacity of the outputs	
• with resistive load, max.	0.5 A; Per digital output
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	12 kΩ
Output voltage	
• for signal "1", min.	23.2 V; L+ (-0.8 V)
Output current	
• for signal "1" rated value	0.5 A; Per digital output
• for signal "1" permissible range, max.	0.6 A; Per digital output
• for signal "1" minimum load current	2 mA
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	50 µs
• "1" to "0", max.	50 µs
Switching frequency	
• with resistive load, max.	10 kHz

<ul style="list-style-type: none"> • with inductive load, max. • on lamp load, max. 	0.5 Hz; Acc. to IEC 60947-5-1, DC-13; observe derating curve 10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> • Current per module, max. 	1 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. • unshielded, max. 	1 000 m 600 m
Encoder	
Encoder signals, incremental encoder (symmetrical)	
<ul style="list-style-type: none"> • Input voltage • Input frequency, max. • Counting frequency, max. • Cable length, shielded, max. • Signal filter, parameterizable • Incremental encoder with A/B tracks, 90° phase offset • Incremental encoder with A/B tracks, 90° phase offset and zero track • pulse encoder • Pulse encoder with direction • pulse encoder with one impulse signal per count direction 	RS 422 1 MHz 4 MHz; with quadruple evaluation 32 m; at 1 MHz Yes Yes Yes Yes Yes Yes Yes
Encoder signals, incremental encoder (asymmetrical)	
<ul style="list-style-type: none"> • Input voltage • Input frequency, max. • Counting frequency, max. • Signal filter, parameterizable • Incremental encoder with A/B tracks, 90° phase offset • Incremental encoder with A/B tracks, 90° phase offset and zero track • pulse encoder • pulse encoder with direction • pulse encoder with one impulse signal per count direction 	5 V TTL (push-pull encoders only) 1 MHz 4 MHz; with quadruple evaluation Yes Yes Yes Yes Yes Yes Yes
Encoder signals, absolute encoder (SSI)	
<ul style="list-style-type: none"> • Input signal • Telegram length, parameterizable • Clock frequency, max. • Binary code • Gray code • Cable length, shielded, max. • Parity bit, parameterizable • Monoflop time • Multiturn • Singleturn 	to RS-422 10 ... 40 bit 2 MHz; 125 kHz, 250 kHz, 500 kHz, 1 MHz, 1.5 MHz or 2 MHz Yes Yes 320 m; Cable length, RS-422 SSI absolute encoders, Siemens type 6FX2001-5, 24 V supply: 125 kHz, 320 meters shielded, max.; 250 kHz, 160 meters shielded, max.; 500 kHz, 60 meters shielded, max.; 1 MHz, 20 meters shielded, max. 1.5 MHz, 10 meters shielded, max.; 2 MHz, 8 meters shielded, max. Yes 16, 32, 48, 64 μs & automatic Yes Yes
Interface types	
<ul style="list-style-type: none"> • TTL 5 V • RS 422 	Yes; push-pull encoders only Yes
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; Parameterizable
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Hardware interrupt 	Yes Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage • Wire-break • Short-circuit • A/B transition error at incremental encoder • Telegram error at SSI encoder • Group error 	Yes Yes Yes Yes Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED

<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red DIAG LED
<ul style="list-style-type: none"> • Status indicator forward counting (green) 	Yes
<ul style="list-style-type: none"> • Status indicator backward counting (green) 	Yes
Integrated Functions	
Counter	Yes
<ul style="list-style-type: none"> • Number of counters 	1
<ul style="list-style-type: none"> • Counting frequency, max. 	4 MHz; with quadruple evaluation
Fast mode	Yes
Counting functions	
<ul style="list-style-type: none"> • Can be used with TO High_Speed_Counter 	Yes; only for pulse and incremental encoders
<ul style="list-style-type: none"> • Continuous counting 	Yes
<ul style="list-style-type: none"> • Counter response parameterizable 	Yes
<ul style="list-style-type: none"> • Hardware gate via digital input 	Yes
<ul style="list-style-type: none"> • Software gate 	Yes
<ul style="list-style-type: none"> • Event-controlled stop 	Yes
<ul style="list-style-type: none"> • Synchronization via digital input 	Yes
<ul style="list-style-type: none"> • Counting range, parameterizable 	Yes
Comparator	
<ul style="list-style-type: none"> — Number of comparators 	2
<ul style="list-style-type: none"> — Direction dependency 	Yes
<ul style="list-style-type: none"> — Can be changed from user program 	Yes
Position detection	
<ul style="list-style-type: none"> • Incremental acquisition 	Yes
<ul style="list-style-type: none"> • Absolute acquisition 	Yes
<ul style="list-style-type: none"> • Suitable for S7-1500 Motion Control 	Yes
Measuring functions	
<ul style="list-style-type: none"> • Measuring time, parameterizable 	Yes
<ul style="list-style-type: none"> • Dynamic measurement period adjustment 	Yes
<ul style="list-style-type: none"> • Number of thresholds, parameterizable 	2
Measuring range	
<ul style="list-style-type: none"> — Frequency measurement, min. 	0.04 Hz
<ul style="list-style-type: none"> — Frequency measurement, max. 	4 MHz
<ul style="list-style-type: none"> — Cycle duration measurement, min. 	0.25 μ s
<ul style="list-style-type: none"> — Cycle duration measurement, max. 	25 s
Accuracy	
<ul style="list-style-type: none"> — Frequency measurement 	100 ppm; depending on measuring interval and signal evaluation
<ul style="list-style-type: none"> — Cycle duration measurement 	100 ppm; depending on measuring interval and signal evaluation
<ul style="list-style-type: none"> — Velocity measurement 	100 ppm; depending on measuring interval and signal evaluation
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. 	-30 °C
<ul style="list-style-type: none"> • horizontal installation, max. 	60 °C; Observe derating
<ul style="list-style-type: none"> • vertical installation, min. 	-30 °C
<ul style="list-style-type: none"> • vertical installation, max. 	50 °C; Observe derating
<ul style="list-style-type: none"> • ceiling installation, min. 	-30 °C
<ul style="list-style-type: none"> • ceiling installation, max. 	50 °C; Observe derating
<ul style="list-style-type: none"> • floor installation, min. 	-30 °C
<ul style="list-style-type: none"> • floor installation, max. 	50 °C; Observe derating
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Decentralized operation	
to SIMATIC S7-300	Yes

to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	45 g

last modified: 8/7/2023 