



SIMATIC ET 200AL, IO-Link, DI 8x 24 V DC, 8x M8, Degree of protection IP67

General information	
Product type designation	IO-Link DI 8x24VDC
HW functional status	FS01
Firmware version	V1.0.x
Vendor identification (VendorID)	42
Device identifier (DeviceID)	229379
Engineering with	
<ul style="list-style-type: none"> • IODD file 	Yes
Supply voltage	
Load voltage 1L+	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V; Supply from 1Us+ of the IO-Link master
<ul style="list-style-type: none"> • permissible range, lower limit (DC) 	18 V
<ul style="list-style-type: none"> • permissible range, upper limit (DC) 	30 V
<ul style="list-style-type: none"> • Reverse polarity protection 	Yes; Against destruction; encoder power supply outputs applied with reversed polarity
Input current	
Current consumption (rated value)	15 mA; without load
Encoder supply	
Number of outputs	8; Supply from 1Us+ of the IO-Link master
24 V encoder supply	
<ul style="list-style-type: none"> • Short-circuit protection 	Yes; per module, electronic
<ul style="list-style-type: none"> • Output current, max. 	0.7 A; Total current of all encoders (depending on IO-Link master supply via 1Us+)
Power loss	
Power loss, typ.	1.5 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	8
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • for signal "0" 	-30 to +5 V
<ul style="list-style-type: none"> • for signal "1" 	+11 to +30V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	3 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	1.2 ms

— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
IO-Link	
IO-Link protocol 1.1	Yes
Transmission rate	38.4 kBd (COM2)
Cycle time, min.	2.1 ms
Size of process data, input per module	1 byte
Size of process data, output per module	0 byte
Supported IO-Link profiles	common profile
Cable length unshielded, max.	20 m
Connection of IO-Link devices	
• Port type A	Yes
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnoses	
• Short-circuit	Yes; Sensor supply to M; module by module
Diagnostics indication LED	
• Channel status display	Yes; green LED
• for module diagnostics	Yes; green/red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Ambient conditions	
Ambient temperature during operation	
• min.	-30 °C
• max.	55 °C
connection method	
Design of electrical connection for the inputs and outputs	M8, 3-pole
Type of electrical connection for IO-Link	M12, 5-pin, A-coded
Dimensions	
Width	30 mm
Height	159 mm
Depth	40 mm
Weights	
Weight, approx.	124 g

last modified: 8/27/2023 