




SIMATIC ET 200SP, BusAdapter BA 2xSCRJ, 2 SCRJ FO connections

| General information                             |   |
|---|---|
| Product type designation                        | BA 2xSCRJ   |
| HW functional status                            | from FS04   |
| Interfaces                                      |   |
| Number of PROFINET interfaces                   | 1; 2 ports (switch) SCRJ FO   |
| Supports protocol for PROFINET IO               |   |
| • Number of SCRJ ports                          | 2   |
| Cable length                                    |   |
| — PCF   | 100 m   |
| — Plastic FOC (POF)                             | 50 m  |
| Ambient conditions                              |   |
| Ambient temperature during operation            |   |
| • horizontal installation, min.                 | -25 °C  |
| • horizontal installation, max.                 | 60 °C   |
| • vertical installation, min.                   | -25 °C  |
| • vertical installation, max.                   | 50 °C   |
| Altitude during operation relating to sea level |   |
| • Installation altitude above sea level, max.   | 5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual        |
| Dimensions                                      |   |
| Width   | 20 mm   |
| Height  | 69.5 mm   |
| Depth   | 59 mm   |
| Weights   |   |
| Weight, approx.                                 | 50 g  |
| last modified:                                  | 8/16/2023  |