



SIMATIC S7-300, Digital input SM 321, isolated, 16 DI, 48-125 V DC, 1x 20-pole

Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	48 V
• permissible range, lower limit (DC)	48 V
• permissible range, upper limit (DC)	125 V
Input current	
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	4.3 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	8
— up to 60 °C, max.	8; 6 to Ue 146 V
vertical installation	
— up to 40 °C, max.	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	48 V; 48 V DC to 125 V DC
• for signal "0"	-146 V DC to +15 V DC
• for signal "1"	30 V DC to 146 V DC
Input current	
• for signal "1", typ.	3.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	0.1 ms
— at "0" to "1", max.	3.5 ms
— at "1" to "0", min.	0.7 ms
— at "1" to "0", max.	3 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	

<ul style="list-style-type: none"> <li>• 2-wire sensor <ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul>	Yes 1 mA
<b>Interrupts/diagnostics/status information</b>	
Alarms	No
Diagnostics function	No
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Hardware interrupt</li> </ul>	No No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• Group error SF (red)</li> <li>• Status indicator digital input (green)</li> </ul>	No Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels, in groups of</li> <li>• between the channels and backplane bus</li> </ul>	No 8 Yes; Optocoupler
<b>Isolation</b>	
Isolation tested with	1 500 V DC
<b>connection method / header</b>	
required front connector	20-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	200 g
<b>last modified:</b>	12/16/2020 