



***** Replacement part ***** SIMATIC S7-400H, CPU 412-3H
 Central processing unit for S7-400H and S7-400F/FH, 3 interfaces: 1
 MPI/DP and 2 for sync modules, 768 KB memory (256 KB data/512 KB
 program)

General information	
Product type designation	CPU 412-3H PN/DP
HW functional status	1
Firmware version	V4.5
Product function	
• Isochronous mode	No
Engineering with	
• Programming package	STEP 7 V5.3 SP2 or higher with HW update
CiR - Configuration in RUN	
CiR synchronization time, basic load	150 ms
CiR synchronization time, time per I/O byte	40 µs
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1.2 A
from backplane bus 5 V DC, max.	1.5 A
from backplane bus 24 V DC, max.	150 mA; Per DP interface
from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	5.5 W
Memory	
Type of memory	RAM
Work memory	
• integrated	768 kbyte
• integrated (for program)	512 kbyte
• integrated (for data)	256 kbyte
• expandable	No
Load memory	
• expandable FEPRM	Yes
• expandable FEPRM, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes
• expandable RAM, max.	64 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data
• without battery	No
Battery	
Backup battery	

<ul style="list-style-type: none"> • Backup current, typ. • Backup current, max. • Backup time, max. 	190 μ A; Valid up to 40°C 660 μ A Dealt with in the module data manual with the secondary conditions and the factors of influence
<ul style="list-style-type: none"> • Feeding of external backup voltage to CPU 	5 V DC to 15 V DC

CPU processing times

for bit operations, typ.	0.075 μ s
for word operations, typ.	0.075 μ s
for fixed point arithmetic, typ.	0.075 μ s
for floating point arithmetic, typ.	0.225 μ s

CPU-blocks

DB	
<ul style="list-style-type: none"> • Number, max. • Size, max. 	4 095; Number range: 1 to 4095 64 kbyte
FB	
<ul style="list-style-type: none"> • Number, max. • Size, max. 	2 048; Number range: 0 to 2047 64 kbyte
FC	
<ul style="list-style-type: none"> • Number, max. • Size, max. 	2 048; Number range: 0 to 2047 64 kbyte
OB	
<ul style="list-style-type: none"> • Size, max. • Number of time alarm OBs • Number of delay alarm OBs • Number of cyclic interrupt OBs • Number of process alarm OBs 	64 kbyte 4 4 4 4
Nesting depth	
<ul style="list-style-type: none"> • per priority class • additional within an error OB 	24 1

Counters, timers and their retentivity

S7 counter	
<ul style="list-style-type: none"> • Number 	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
<ul style="list-style-type: none"> • present • Type 	Yes SFB
S7 times	
<ul style="list-style-type: none"> • Number 	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
<ul style="list-style-type: none"> • present • Type 	Yes SFB

Data areas and their retentivity

Retentive data area (incl. timers, counters, flags), max.	Total working and load memory (with backup battery)
Flag	
<ul style="list-style-type: none"> • Size, max. 	8 kbyte

<ul style="list-style-type: none"> • Retentivity available • Retentivity preset • Number of clock memories 	Yes MB 0 to MB 15 8; in 1 memory byte
Local data	
<ul style="list-style-type: none"> • adjustable, max. • preset 	16 kbyte 8 kbyte
Address area	
I/O address area	
<ul style="list-style-type: none"> • Inputs • Outputs 	8 kbyte 8 kbyte
Process image	
<ul style="list-style-type: none"> • Inputs, adjustable • Outputs, adjustable • Inputs, default • Outputs, default • consistent data, max. • Access to consistent data in process image 	8 kbyte 8 kbyte 256 byte 256 byte 244 byte Yes
Subprocess images	
<ul style="list-style-type: none"> • Number of subprocess images, max. 	15
Digital channels	
<ul style="list-style-type: none"> • Inputs <ul style="list-style-type: none"> — of which central • Outputs <ul style="list-style-type: none"> — of which central 	65 536 65 536 65 536 65 536
Analog channels	
<ul style="list-style-type: none"> • Inputs <ul style="list-style-type: none"> — of which central • Outputs <ul style="list-style-type: none"> — of which central 	4 096 4 096 4 096 4 096
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	15 without message processing, 8 with message processing
Multicomputing	No
Interface modules	
<ul style="list-style-type: none"> • Number of connectable IMs (total), max. • Number of connectable IM 460s, max. • Number of connectable IM 463s, max. 	6 6 4; Single mode only
Number of DP masters	
<ul style="list-style-type: none"> • integrated • via CP • Mixed mode IM + CP permitted • via interface module 	1 10 No 0
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> • FM • CP, PtP • PROFIBUS and Ethernet CPs 	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections 14; Of which max. 10 CP as DP master
Slots	
<ul style="list-style-type: none"> • required slots 	2
Time of day	
Clock	
<ul style="list-style-type: none"> • Hardware clock (real-time) • retentive and synchronizable • Resolution • Deviation per day (buffered), max. • Deviation per day (unbuffered), max. 	Yes Yes 1 ms 1.7 s; Power off 8.6 s; Power on
Operating hours counter	
<ul style="list-style-type: none"> • Number • Number/Number range 	8 0 to 7

<ul style="list-style-type: none"> • Range of values • Granularity • retentive 	<p>0 to 32767 hours</p> <p>1 h</p> <p>Yes</p>
Clock synchronization	
<ul style="list-style-type: none"> • supported • to MPI, master • to MPI, slave • to DP, master • to DP, slave • in AS, master • in AS, slave 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Time difference in system when synchronizing via	
<ul style="list-style-type: none"> • MPI, max. 	200 ms
Interfaces	
Number of RS 485 interfaces	2
Number of other interfaces	0
Optical interface	No
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
<ul style="list-style-type: none"> • RS 485 • Output current of the interface, max. 	<p>Yes</p> <p>150 mA</p>
Protocols	
<ul style="list-style-type: none"> • MPI • PROFIBUS DP master • PROFIBUS DP slave 	<p>Yes</p> <p>Yes</p> <p>No</p>
MPI	
<ul style="list-style-type: none"> • Number of connections • Transmission rate, max. 	<p>16</p> <p>12 Mbit/s</p>
Services	
<ul style="list-style-type: none"> — PG/OP communication — Routing — Global data communication — S7 basic communication — S7 communication 	<p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p>
PROFIBUS DP master	
<ul style="list-style-type: none"> • Number of connections, max. • Transmission rate, max. • Number of DP slaves, max. 	<p>16</p> <p>12 Mbit/s</p> <p>32</p>
Services	
<ul style="list-style-type: none"> — PG/OP communication — Routing — Global data communication — S7 basic communication — S7 communication — Equidistance — SYNC/FREEZE — Activation/deactivation of DP slaves — Direct data exchange (slave-to-slave communication) 	<p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
Address area	
<ul style="list-style-type: none"> — Inputs, max. — Outputs, max. 	<p>2 kbyte</p> <p>2 kbyte</p>
User data per DP slave	
<ul style="list-style-type: none"> — User data per DP slave, max. — Inputs, max. — Outputs, max. — Slots, max. — per slot, max. 	<p>244 byte</p> <p>244 byte</p> <p>244 byte</p> <p>244</p> <p>128 byte</p>

PROFIBUS DP slave	
• Number of connections	No configuration of CPU as DP slave
3. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization submodule IF 960 6ES7960-1AA04-0XA0
4. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization submodule IF 960 6ES7960-1AA04-0XA0
Protocols	
SIMATIC communication	
• S7 routing	Yes
Isochronous mode	
Equidistance	No
communication functions / header	
PG/OP communication	
• Number of connectable OPs without message processing	15
• Number of connectable OPs with message processing	8
Global data communication	
• supported	No
S7 basic communication	
• supported	No
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
• User data per job (of which consistent), max.	462 byte; 1 variable
S5 compatible communication	
• supported	Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)
• User data per job, max.	8 kbyte
• User data per job (of which consistent), max.	240 byte
• Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.	24/24
Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
Number of connections	
• overall	16
• usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
• usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
• usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
• usable for S7 communication	
— reserved for S7 communication	0
— adjustable for S7 communication, max.	0
• usable for routing	
— reserved for routing	0
— adjustable for routing, max.	0
S7 message functions	
Number of login stations for message functions, max.	8
Symbol-related messages	No
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	100
Alarm 8-blocks	Yes

<ul style="list-style-type: none"> • Number of instances for alarm 8 and S7 communication blocks, max. 	600
<ul style="list-style-type: none"> • preset, max. 	300
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	16
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> • Status/control variable 	Yes
<ul style="list-style-type: none"> • Variables 	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
<ul style="list-style-type: none"> • Number of variables, max. 	70
Forcing	
<ul style="list-style-type: none"> • Forcing 	Yes
<ul style="list-style-type: none"> • Forcing, variables 	Inputs/outputs, bit memories, distributed I/Os
<ul style="list-style-type: none"> • Number of variables, max. 	256
Diagnostic buffer	
<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • Number of entries, max. 	3 200
<ul style="list-style-type: none"> — adjustable 	Yes
<ul style="list-style-type: none"> — preset 	120
configuration / header	
Configuration software	
<ul style="list-style-type: none"> • STEP 7 	Yes
configuration / programming / header	
<ul style="list-style-type: none"> • Command set 	see instruction list
<ul style="list-style-type: none"> • Nesting levels 	8
<ul style="list-style-type: none"> • Access to consistent data in process image 	Yes
<ul style="list-style-type: none"> • System functions (SFC) 	see instruction list
<ul style="list-style-type: none"> • System function blocks (SFB) 	see instruction list
Programming language	
<ul style="list-style-type: none"> — LAD 	Yes
<ul style="list-style-type: none"> — FBD 	Yes
<ul style="list-style-type: none"> — STL 	Yes
<ul style="list-style-type: none"> — SCL 	Yes
<ul style="list-style-type: none"> — CFC 	Yes
<ul style="list-style-type: none"> — GRAPH 	Yes
<ul style="list-style-type: none"> — HiGraph® 	Yes
configuration / programming / number of simultaneously active SFC / header	
<ul style="list-style-type: none"> — RD_REC 	8
<ul style="list-style-type: none"> — WR_REC 	8
<ul style="list-style-type: none"> — WR_PARM 	8
<ul style="list-style-type: none"> — PARM_MOD 	1
<ul style="list-style-type: none"> — WR_DPARM 	2
<ul style="list-style-type: none"> — DPNRM_DG 	8
<ul style="list-style-type: none"> — RDSYSST 	8
<ul style="list-style-type: none"> — DP_TOPO 	1
configuration / programming / number of simultaneously active SFB / header	
<ul style="list-style-type: none"> — RDREC 	8
<ul style="list-style-type: none"> — WRREC 	8
Know-how protection	
<ul style="list-style-type: none"> • User program protection/password protection 	Yes
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	990 g

last modified:

7/28/2021 