



Figure similar

TERM. BLOCK TPOO W. LED SCREW TERM.

Connection module TPOO w. optocoupler 24 V DC, Output 8 NO contacts  
24V DC/4 A Overload and short circuit-proof, with LED Push-in terminal  
VPE = 1 unit 16 pole IDC connection for cable

target system	SIMATIC S7-300 / 1500
suitability for use	Digital output module
product type designation	Fully modular connection
product designation	Connection module
<b>Operating data / header</b>	
operating voltage	
• at DC / rated value	24 V; for coil
• rated value	50 V
• at DC / maximum	28.8 V
• at AC / rated value	for coil
current / rated value	1 A
continuous current / at DC / per signal cable / maximum	4 A
total current / maximum	32 A; any, except overhead; voltage feed each group of four max. 16A
switching capacity current / of the contacts / with resistive load / maximum	4 A; for 24V DC
operating temperature	0 ... 60 °C
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
number of terminal levels	1
number of terminal points / per terminal level	1
number of terminals	22; 8 x O; 2 x L+, 2 x M; 10 x special terminals
type of connecting terminal	Screw-type terminal
type of electrical connection / for actuators and sensors	Screw-type terminal
position / of the terminal	Top
design of LED initiator/actuator terminal	Screw-type terminal
width of screwdriver blade	3.5 mm
tightening torque / with screw-type terminals	0.4 ... 0.5 N·m
design of terminal / terminal levels internally linked	No
product component	
• PE connection	No
• shield connection	No
• disconnecter	No
• required / end cover plate	No
product function / infeed function	Yes
product feature / cross-connectable	No
type of switching contact	Optocoupler
operating frequency / maximum	500 1/s
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the

	sum total of cross sections be achieved in a ferrule.
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	
• for flexible conductor / with core end processing	0.5 ... 2.5 mm <sup>2</sup> ; End sleeve according to DIN 46228/1
• stranded	0.5 ... 2.5 mm <sup>2</sup>
• finely stranded / with core end processing	0.5 ... 2.5 mm <sup>2</sup>
number of poles / at the 1st interface	16; the IDC connector for the connection cable
type of electrical connection / for connecting cable	Plug-in connection
number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module
<b>General data / header</b>	
mounting type	DIN rail 35 mm, DIN rail 15 mm
installation or assembly note	any, head excepted
mounting position	any
degree of pollution	2
overvoltage category	2
combustibility class acc. to UL 94	V1
insulation material	other
design tested acc. to type of protection / EEx e	No
certificate of suitability / cULus approval	Yes
reference code / acc. to IEC 81346-2	X
color	
• of the enclosure	grey
• of the light source	other
length	76 mm
height / of the enclosure	76 mm
width / of the enclosure	130 mm
depth / of the enclosure	60 mm
height / with lowest-profile installation	60 mm
net weight	0.29 kg

