## **SIEMENS**

## **Data sheet**

## 6ES7972-0BA61-0XA0

product type designation	PROFIBUS connector
product type designation product description	PROFIBUS bus connector, RS 485, Fast Connect, without programming port, 35°
F	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 35 degree cable outlet, Insulation displacement method FastConnect, without PG socket 15.8x 54x 39.5 mm (BxHxD)
suitability for use	For connecting PROFIBUS stations to the PROFIBUS bus cable
transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s 12 Mbit/s
interfaces	
number of electrical connections	
for PROFIBUS cables	2
<ul> <li>for network components or terminal equipment</li> </ul>	1
type of electrical connection	
• for PROFIBUS cables	Integrated insulation displacement terminals for 2-core PB FC installation cables
<ul> <li>for network components or terminal equipment</li> </ul>	9-pin sub D connector
type of electrical connection / FastConnect	Yes
mechanical data	
design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint
design, dimensions and weights	
type of cable outlet	35 degree cable outlet
width	15.8 mm
height	54 mm
depth	39.5 mm
net weight	29 g
ambient conditions	
ambient temperature	
during operation	-25 +60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
protection class IP	IP20
product features, product functions, product components / ge	neral
product feature	
• silicon-free	Yes
product component	
PG connection socket	No
strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
RoHS conformity	Yes
UL approval	Yes
reference code	
according to IEC 81346-2	XG
further information / internet links	
internet link	
to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
• • • • • • • • • • • • • • • • • • • •	
last modified:	8/16/2023 🗗