

product type designation



MV320 optical hand-held reader

SIMATIC MV320 optical reader, handheld reader for 1D and 2D codes e.g. data matrix, ready-to-use set from reader and USB cable power supply via USB 6' (1.8 m) for use with codes with medium to high contrast, reading range depending on code type and size 20 mm to 375 mm.

suitability for operation

1D/2D: Aztec, Codabar, Codablock F, Code 11, Code 39, Code 39 Short Margin, Code 39 Extended Full ASCII, Code 39 Checksum, Code 93, Code 128, Code 128 Short Margin, Composite, Data Matrix, Data Matrix Rectangle, Data Matrix Inverse, GS1 DataBar (all), Interleaved 2of5, Interleaved 2of5 - 2 Digits, Macro PDF417, Maxicode, Matrix 2of5, Micro PDF417, MSI Plessey, NEC 2of5, OCR, PDF417, Postal Codes (All), QR Code, Telepen, UPC, UPC Short Margin, UPC Extension

range 20 ... 375 mm

range / note Code-dependent

optical data

design of image sensor / of the camera CMOS 1280 x 960, image resolution 960 x 640

fastening method / of lens Integrated

type of light source Lighting system comprising incident light (red)

picture recording frequency / maximum 10 Hz

type of focusing Fixed focus, optimum focal point at 6.3 mm

supply voltage, current consumption, power loss

type of current supply Via USB or external plug-type power supply unit (RS232), 5 V, 410 mA

type of battery --

ambient conditions

ambient temperature

- during operation -20 ... +55 °C
- during storage -30 ... +65 °C

relative humidity / at 25 °C / without condensation / during operation / maximum 95 %

height of fall / maximum 1.8 m

design, dimensions and weights

width 132 mm

height 52 mm

depth 92 mm

net weight 0.13 kg

product features, product functions, product components / general

design of the display 2 LEDs

operator element version Trigger in handle

design of acoustic signaling element Vibration alarm, audible signal

design of the interface USB, RS232

product functions / management, configuration, engineering

product function / of the software Read, display, save, transfer codes

type of programming Optical parameterization or via configuration software

accessories

accessories RS232 cable with power supply, USB cable, stand

further information / internet links

internet link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>
<http://www.siemens.com/codereader>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

10/11/2023 