

product type designation



Code Reader MV560 U

SIMATIC MV560 U optical reader Resolution: 1920 x 1200 pixels; Maximum processing and communication speed; Function: 1D/2D code reading; Image field and distance: variable (lens); PoE; IP67 with 6GF3540-8ACxx; Delivery: reader; B enable => VSF!

suitability for operation

1D codes: Int. 2/5, Code 128, Code 93, Code 39, Code 32, EAN 13, EAN 8, UPC-A, UPC-E, GS1, Pharmacode, Postnet, 2D codes: DMC, dot code, PDF417 (without: Truncated, Micro and Macro), Q R (without: Micro and Macro), verification uncalibrated

interfaces

type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface of the RS 422 interface of the RS 232 interface for supply voltage at the digital inputs/outputs 	<p>M12, d-coded, PoE</p> <p>M12, 12-pin, male</p> <p>M12, 12-pin, male</p> <p>M12, 12-pin, male</p> <p>M12, 12-pin, male</p>
number of digital inputs	1
number of digital outputs	3
digital input version	1 fast trigger input
digital output version	1 fast strobe output, 2 potential-free outputs (NPN- PNP-capable)

optical data

design of image sensor / of the camera	CMOS chip, 1920 x 1200
type of image capture	Global shutter with manual or automatic exposure time
range	70 ... 3000 mm
range / note	Using C-mount lenses and lens accessories, the range can be exactly matched to the application
fastening method / of lens	C-mount lens connection
type of light source	Integrated lighting or external lighting according to accessories list
picture recording frequency / maximum	60 Hz
code reading rate / maximum	60 1/s
type of focusing	Manual adjustment on the lens

supply voltage, current consumption, power loss

supply voltage	
<ul style="list-style-type: none"> at DC / rated value at DC 	<p>24 V</p> <p>19.2 ... 28.8 V</p>
consumed current / at DC / at 24 V	
<ul style="list-style-type: none"> typical maximum 	<p>0.2 A</p> <p>2 A</p>
buffering time / in the event of power failure / minimum	0.01 s

mechanical data

material	Die-cast aluminum
color	petrol blue

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation 	50 °C

<ul style="list-style-type: none"> during storage 	-30 ... +70 °C
<ul style="list-style-type: none"> during transport 	-30 ... +70 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP67
shock resistance	According to IEC 60068-2
shock acceleration	300 m/s ²
vibrational acceleration	40 m/s ²
design, dimensions and weights	
width	68 mm
height	122 mm
depth	45 mm
net weight	0.55 kg
fastening method	4 x M4 screws
product features, product functions, product components / general	
display version	7 LEDs
protocol / is supported / Media Redundancy Protocol (MRP)	No
product function / of the PROFINET IO device / is supported / H-Sync forwarding	No
protocol / is supported	
<ul style="list-style-type: none"> LLDP 	Yes
<ul style="list-style-type: none"> PROFINET IO protocol 	Yes
<ul style="list-style-type: none"> TCP/IP 	Yes
<ul style="list-style-type: none"> SNMP v1 	Yes
<ul style="list-style-type: none"> SNMP v2 	No
<ul style="list-style-type: none"> SNMP v3 	No
<ul style="list-style-type: none"> DCP 	Yes
<ul style="list-style-type: none"> EtherNet/IP protocol 	No
<ul style="list-style-type: none"> OPC UA 	No
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	CE, NuG suitable
MTBF	66 a
accessories	
accessories	mounting brackets, built-in ring lights, external ring lights, E-focus lens, C-mount lenses, protective barrels for lenses
further information / internet links	
internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/codereader
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAX-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	10/6/2023 