

product type designation

Bus terminal RS 485 (1.5 m)

bus terminal RS 485 for PROFIBUS with plug-in cable 1.5 m.



transfer rate

transfer rate	
<ul style="list-style-type: none"> with PROFIBUS 	9.6 kbit/s ... 1.5 Mbit/s

interfaces

number of electrical connections	
<ul style="list-style-type: none"> for PROFIBUS cables 	2
type of electrical connection	
<ul style="list-style-type: none"> for PROFIBUS cables 	Screw terminals

mechanical data

material / of the enclosure	plastic
-----------------------------	---------

design, dimensions and weights

width	50 mm
height	138 mm
depth	53 mm
net weight	353 g
fastening method	
<ul style="list-style-type: none"> 35 mm top hat DIN rail mounting 	Yes

product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> silicon-free 	Yes

further information / internet links

internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified: 11/9/2023 