

### product type designation



### PROFIBUS OB

PROFIBUS OB; opt. bus terminal for connection of a PROFIBUS nodes without integr. opt. interface to the opt. PROFIBUS DP; without Simplex plug.

transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	3
number of electrical connections	
• for network components or terminal equipment	1
• for power supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for power supply	3-pole terminal block
• for power supply and signaling contact	-
number of optical interfaces / for fiber optic cable	2
design of the optical interface / for fiber optic cable	Duplex port
optical data	
attenuation factor / of the FOC transmission link	
• for PCF FOC with 200/230 μm / at 10 dB/km	3 dB
• for POF FOC with 980/1000 μm / at 230 dB/km	13 dB
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 μm / at 10 dB/km	-16 dB
• of the FOC transmission link / for POF FOC with 980/1000 μm / at 230 dB/km	-5.9 dB
optical sensitivity relating to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 μm / at 10 dB/km	-22 dB
• of the FOC transmission link / for POF FOC with 980/1000 μm / at 230 dB/km	-20 dB
wavelength / of the optical interface / note	660 nm, POF/PCF
wire length	
• for PCF FOC with 200/230 μm / at 10 dB/km / maximum	300 m
• for POF FOC with 980/1000 μm / at 230 dB/km / maximum	50 m
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / at DC / rated value	24 V
supply voltage / at DC	19.2 ... 28.8 V
ambient conditions	
ambient temperature	

<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	<p>0 ... 60 °C</p> <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p>
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP30

### design, dimensions and weights

design	compact
width	50.5 mm
height	138 mm
depth	78 mm
net weight	400 g
fastening method	
<ul style="list-style-type: none"> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> </ul>	<p>Yes</p> <p>Yes</p>

### product functions / redundancy

product function / ring redundancy	No
------------------------------------	----

### standards, specifications, approvals

standard	
<ul style="list-style-type: none"> <li>for safety / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	<p>UL 60950-1, CSA C22.2 Nr. 60950-1</p> <p>EN 61000-6-4 (Class A)</p> <p>EN 61000-6-2</p>
certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> <li>CE marking</li> <li>C-Tick</li> <li>CCC / for hazardous zone according to GB standard</li> </ul>	<p>Yes</p> <p>Yes</p> <p>No</p>
Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> <li>French marine classification society (BV)</li> <li>Det Norske Veritas (DNV)</li> <li>Germanische Lloyd (GL)</li> <li>Lloyds Register of Shipping (LRS)</li> <li>Nippon Kaiji Kyokai (NK)</li> </ul>	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>

### further information / internet links

internet link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<p><a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a></p> <p><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></p> <p><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></p> <p><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></p> <p><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></p> <p><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>

### security information

security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)
----------------------	--

### Approvals / Certificates

General Product Approval	EMC	For use in hazardous locations
--------------------------	-----	--------------------------------

[Manufacturer Declaration](#)



[Explosion Protection Certificate](#)

[ATEX-Zone 2-Declaration](#)



[FM](#)

For use in hazardous locations

Declaration of Conformity

Marine / Shipping

[CCC-Ex](#)



[Manufacturer Declaration](#)



Marine / Shipping

Environment



[NK / Nippon Kaiji Kyokai](#)



last modified:

11/9/2023