

### product type designation

### PROFIBUS OLM/G12 V4.0

PROFIBUS OLM/G12 V4.0 Optical Link Module with 1 RS 485 and 2 glass FOC interfaces (4 BFOC sockets) for standard Distances up to 2850 m, with signaling contact and measuring output.



transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	3
number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
number of optical interfaces / for fiber optic cable	2
design of the optical interface / for fiber optic cable	BFOC port
optical data	
attenuation factor / of the FOC transmission link	
• for glass FOC with 50/125 $\mu\text{m}$ / at 3 dB/km / maximum	10 dB
• for glass FOC with 62.5/125 $\mu\text{m}$ / at 3.5 dB/km / maximum	12 dB
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• for glass FOC with 50/125 $\mu\text{m}$ / at 3 dB/km	-16 dB
• for glass FOC with 62.5/125 $\mu\text{m}$ / at 3.5 dB/km	-13 dB
optical sensitivity relating to 1 mW	
• for glass FOC with 50/125 $\mu\text{m}$ / at 3 dB/km	-28 dB
• for glass FOC with 62.5/125 $\mu\text{m}$ / at 3.5 dB/km	-28 dB
wavelength / of the optical interface / note	860 nm, multimode
wire length	
• for glass FOC with 50/125 $\mu\text{m}$ / at 3 dB/km / maximum	3 km
• for glass FOC with 62.5/125 $\mu\text{m}$ / at 3.5 dB/km / maximum	3 km
signal inputs/outputs	
operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC

supply voltage / at DC / rated value	24 V
supply voltage / at DC	18.8 ... 28.8 V
product component / fusing at power supply input	Yes
consumed current / at DC / at 24 V / maximum	0.2 A
<b>ambient conditions</b>	
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40
<b>design, dimensions and weights</b>	
design	compact
width	39.5 mm
height	112 mm
depth	74.5 mm
net weight	340 g
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
<b>product functions / redundancy</b>	
product function / ring redundancy	Yes
<b>standards, specifications, approvals</b>	
standard	
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• CE marking	Yes
• C-Tick	Yes
• CCC / for hazardous zone according to GB standard	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• French marine classification society (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
<b>further information / internet links</b>	
internet link	
• to web page: selection aid TIA Selection Tool	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAX-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)
<b>Approvals / Certificates</b>	

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------

[Manufacturer Declaration](#)



[Miscellaneous](#)



[Manufacturer Declaration](#)

Declaration of Conformity	Marine / Shipping
---------------------------	-------------------



Marine / Shipping	Environment
-------------------	-------------

[NK / Nippon Kaiji Kyokai](#)



last modified:

11/9/2023