

### product type designation

### PROFIBUS OLM/P22 V4.1

PROFIBUS OLM/P22 V4.1 Optical link module with 2 RS 485 and 3 plastic FOC interfaces (4 BFOC sockets); with signaling contact and test port



transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical connections	
• for network components or terminal equipment	2
• for measuring device	1
• for signaling contact	1
• for power supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
design of the optical interface / for fiber optic cable	BFOC port
optical data	
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 $\mu\text{m}$ / at 10 dB/km	-17 dB
• of the FOC transmission link / for POF FOC with 980/1000 $\mu\text{m}$ / at 230 dB/km	-5 dB
optical sensitivity relating to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 $\mu\text{m}$ / at 10 dB/km	-23 dB
wire length	
• for PCF FOC with 200/230 $\mu\text{m}$ / at 10 dB/km / maximum	400 m
• for POF FOC with 980/1000 $\mu\text{m}$ / at 230 dB/km / maximum	80 m
signal inputs/outputs	
operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / at DC / rated value	24 V
supply voltage / at DC	18 ... 32 V
product component / fusing at power supply input	Yes
consumed current / at DC / at 24 V / maximum	0.2 A
ambient conditions	

ambient temperature		
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C	
relative humidity		
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %	
protection class IP	IP40	
<b>design, dimensions and weights</b>		
design	compact	
width	39.5 mm	
height	112 mm	
depth	74.5 mm	
net weight	0.34 kg	
fastening method		
<ul style="list-style-type: none"> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> </ul>	Yes Yes	
<b>product functions / redundancy</b>		
product function / ring redundancy	Yes	
<b>standards, specifications, approvals</b>		
standard		
<ul style="list-style-type: none"> <li>for safety / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	UL 60950-1, CSA C22.2 Nr. 60950-1 EN 61000-6-4 (Class A) EN 61000-6-2	
certificate of suitability	EN 61000-6-2, EN 61000-6-4	
<ul style="list-style-type: none"> <li>CE marking</li> <li>C-Tick</li> <li>CCC / for hazardous zone according to GB standard</li> </ul>	Yes Yes No	
Marine classification association		
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> <li>French marine classification society (BV)</li> <li>Det Norske Veritas (DNV)</li> <li>Germanische Lloyd (GL)</li> <li>Lloyds Register of Shipping (LRS)</li> <li>Nippon Kaiji Kyokai (NK)</li> </ul>	Yes Yes Yes Yes Yes Yes	
<b>further information / internet links</b>		
internet link		
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/blddb">http://automation.siemens.com/blddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>	
<b>security information</b>		
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>	
<b>Approvals / Certificates</b>		
General Product Approval	EMC	Declaration of Conformity

[Manufacturer Declaration](#)



[Manufacturer Declaration](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



Marine / Shipping

Environment



last modified:

11/9/2023