6GK5108-0BA00-2AC2

Data sheet



SCALANCE XC108, Unmanaged IE switch, $8x\ 10/100\ Mbit/s\ RJ45\ ports$, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download .

product type designation	SCALANCE XC108
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	8
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	8; RJ45
interfaces / other	
number of electrical connections	
 for signaling contact 	1
for power supply	1
type of electrical connection	
• for signaling contact	2-pole terminal block
for power supply	4-pole terminal block
signal inputs/outputs	
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	3 W
 consumed current / 1 / at rated supply voltage / maximum 	0.25 A
supply voltage / 1 / rated value	9.6 31.2 V
 type of electrical connection / 1 / for power supply 	4-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
fuse protection type / 1 / at input for supply voltage	2.5 A / 125 V
ambient conditions	
ambient temperature	
during operation	-40 +70 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	

docian	compact
design width	60 mm
	147 mm
height	125 mm
depth	0.475 kg
net weight material / of the enclosure	Polycarbonate (PC-GF10)
	Polycarbonate (PC-GP10)
fastening method	Yes
35 mm top hat DIN rail mounting wall mounting	Yes
wall mounting S7 200 roll mounting	Yes
S7-300 rail mountingS7-1500 rail mounting	Yes
product features, product functions, product components / gen-	
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineering	
product function	Ma
multiport mirroring	No
• CoS	Yes
product function / switch-managed	No
product function	Voc
• is supported / identification link	Yes
product functions / redundancy	
product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
standard	
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
for emitted interference	EN 61000-6-4 (Class B)
reference code	
according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,
• from CSA and UL	KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010 UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A,
contificate of quitability	B, C, D / T, Class 1 / Zone 2 / Group IIC / T
certificate of suitability • CCC / for hazardous zone according to GB standard	Yes
CCC / for hazardous zone according to GB standard CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc
CCC / for nazardous zone according to GB standard / as marking	EXTINUIO 14 OC
standards, specifications, approvals / other	
laser protection class	LED Class 1
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
KC approval	Yes
• E1 approval	Yes
 EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1 	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	Yes
 French marine classification society (BV) 	Yes
• DNV GL	Yes
 Korean Register of Shipping (KRS) 	Yes
Lloyds Register of Shipping (LRS)	Yes
	Yes
 Polski Rejestr Statkow (PRS) 	
Royal Institution of Naval Architects (RINA)	Yes
	The state of the s

Yes **Environmental Product Declaration** • Global Warming Potential [CO2 eq] / total 153.7 kg • Global Warming Potential [CO2 eq] / during 28.4 kg manufacturing • Global Warming Potential [CO2 eq] / during operation 125.2 kg • global warming potential [CO2 eq] / after end of life 0.02 kg

internet link

• to web page: selection aid TIA Selection Tool

• to website: Industrial communication

to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

http://www.siemens.com/tia-selection-tool

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-ofthe-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit

https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)

Approvals / Certificates

General Product Approval

EMC

For use in hazardous locations

Manufacturer Declaration

<u>FM</u>



Miscellaneous



ATEX-Zone 2-Declaration



For use in hazardous locations

CCC-Ex





Declaration of Conformity

Manufacturer Declaration



Test Certificates

Marine / Shipping

inspection certificate







NK / Nippon Kaiji Ky-



Marine / Shipping





Manufacturer Declaration

other



Environment

Environmental Confirmations







last modified: 10/27/2023 🖸