



SCALANCE X308-2M; managed IE switch, compact; 4x 10/100/1000 Mbit/s for RJ45 ports electrical; 2x 100/1000 Mbit/s for 2-port media modules, electrical or optical; LED diagnostics; error signaling contact; select/set pushbutton; PROFINET IO device; network management; Integrated redundancy manager; office features (RSTP, VLAN, IGMP,...); C-PLUG in scope of supply.

|  |  |
|--|--|
| <b>product type designation</b>  | <b>SCALANCE X308-2M</b>  |
| <b>transfer rate</b>   |  |
| transfer rate  | 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s                                     |
| <b>interfaces / for communication / maximum configuration for modular devices</b>  |  |
| number of electrical ports / maximum   | 8  |
| number of optical ports / maximum  | 4  |
| <b>interfaces / for communication / integrated</b>   |  |
| number of electrical connections <ul style="list-style-type: none"> <li>• for network components or terminal equipment</li> </ul>  | 4  |
| number of 10/100/1000 Mbit/s RJ45 ports / integrated <ul style="list-style-type: none"> <li>• with securing collar</li> </ul>  | 4  |
| number of connectable media modules <ul style="list-style-type: none"> <li>• with 2 ports</li> </ul>   | 2  |
| <b>interfaces / other</b>  |  |
| number of electrical connections <ul style="list-style-type: none"> <li>• for signaling contact</li> <li>• for media module</li> <li>• for power supply</li> </ul>   | 1<br>2<br>1  |
| type of electrical connection <ul style="list-style-type: none"> <li>• for signaling contact</li> <li>• for power supply</li> </ul>  | 2-pole terminal block<br>4-pole terminal block                         |
| design of the removable storage <ul style="list-style-type: none"> <li>• C-PLUG</li> </ul>   | Yes  |
| <b>signal inputs/outputs</b>   |  |
| operating voltage / of the signaling contacts <ul style="list-style-type: none"> <li>• at DC / rated value</li> </ul>  | 24 V   |
| operational current / of the signaling contacts <ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>  | 0.1 A  |
| <b>supply voltage, current consumption, power loss</b>   |  |
| product component / connection for redundant voltage supply  | Yes  |
| type of voltage supply / redundant power supply unit   | No   |
| <b>type of voltage / 1 / of the supply voltage</b>   | DC   |
| <ul style="list-style-type: none"> <li>• supply voltage / 1 / rated value</li> <li>• power loss [W] / 1 / rated value</li> <li>• supply voltage / 1 / rated value</li> <li>• consumed current / 1 / maximum</li> <li>• type of electrical connection / 1 / for power supply</li> <li>• product component / 1 / fusing at power supply input</li> </ul> | 24 V<br>16.6 W<br>18 ... 32 V<br>0.7 A<br>4-pole terminal block<br>Yes |
| <b>ambient conditions</b>  |  |
| ambient temperature  |  |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> <li>note</li> </ul>  | <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p> <p>Reduced operating temperature through the use of media modules (-40 °C to +70 °C) or SFP plug-in transceivers (-40 °C to +60 °C). If the device is installed in the vertical position, the maximum operating temperature is reduced to +50 °C.</p> |
| <p>relative humidity</p> <ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>   | 95 %  |
| protection class IP   | IP20  |
| <b>design, dimensions and weights</b>   |   |
| design  | compact   |
| width   | 120 mm  |
| height  | 125 mm  |
| depth   | 124 mm  |
| net weight  | 1.4 kg  |
| fastening method  | When used in shipbuilding, installation on a 35 mm standard mounting rail is not permitted.   |
| <ul style="list-style-type: none"> <li>19-inch installation</li> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> <li>S7-300 rail mounting</li> <li>S7-1500 rail mounting</li> </ul>   | <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p>  |
| <b>product features, product functions, product components / general</b>  |   |
| cascading in the case of a redundant ring / at reconfiguration time of <math>\leq 0.3</math> s  | 100   |
| cascading in cases of star topology   | any (depending only on signal propagation time)   |
| <b>product functions / management, configuration, engineering</b>   |   |
| product function  |   |
| <ul style="list-style-type: none"> <li>CLI</li> <li>web-based management</li> <li>MIB support</li> <li>TRAPs via email</li> <li>configuration with STEP 7</li> <li>RMON</li> <li>port mirroring</li> <li>multiport mirroring</li> <li>CoS</li> <li>PROFINET IO diagnosis</li> </ul> | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>  |
| PROFINET conformity class   | B   |
| product function / switch-managed   | Yes   |
| protocol / is supported   |   |
| <ul style="list-style-type: none"> <li>Telnet</li> <li>HTTP</li> <li>HTTPS</li> <li>TFTP</li> <li>FTP</li> <li>BOOTP</li> <li>GMRP</li> <li>DCP</li> <li>LLDP</li> <li>SNMP v1</li> <li>SNMP v2</li> <li>SNMP v3</li> <li>IGMP (snooping/querier)</li> </ul>                        | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>   |
| identification & maintenance function   |   |
| <ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> <li>I&amp;M1 - higher level designation/location designation</li> </ul>  | <p>Yes</p> <p>Yes</p>   |
| <b>product functions / diagnostics</b>  |   |
| product function  |   |
| <ul style="list-style-type: none"> <li>port diagnostics</li> </ul>  | Yes   |

|   |     |
|---|-----|
| <ul style="list-style-type: none"> <li>• statistics Packet Size</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• statistics packet type</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• error statistics</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• SysLog</li> </ul>  | Yes |
| <b>product functions / VLAN</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>• VLAN - port based</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• VLAN - protocol-based</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>• VLAN - IP-based</li> </ul>   | No  |
| <ul style="list-style-type: none"> <li>• VLAN dynamic</li> </ul>  | Yes |
| number of VLANs / maximum   | 255 |
| number of VLANs - dynamic / maximum   | 255 |
| protocol / is supported / GVRP  | Yes |
| <b>product functions / DHCP</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>• DHCP client</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• DHCP Option 66</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• DHCP Option 67</li> </ul>  | Yes |
| <b>product functions / redundancy</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>• ring redundancy</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• High Speed Redundancy Protocol (HRP)</li> </ul>                              | Yes |
| <ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with redundancy manager</li> </ul>      | Yes |
| <ul style="list-style-type: none"> <li>• high speed redundancy protocol (HRP) with standby redundancy</li> </ul>      | Yes |
| protocol / is supported / Media Redundancy Protocol (MRP)   | Yes |
| product function  |     |
| <ul style="list-style-type: none"> <li>• media redundancy protocol (MRP) with redundancy manager</li> </ul>           | Yes |
| <ul style="list-style-type: none"> <li>• redundancy procedure STP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• redundancy procedure RSTP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• redundancy procedure MSTP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul> | No  |
| <ul style="list-style-type: none"> <li>• passive listening</li> </ul>   | Yes |
| protocol / is supported   |     |
| <ul style="list-style-type: none"> <li>• STP/RSTP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• STP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• RSTP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• MSTP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• RSTP big network support</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• LACP</li> </ul>  | Yes |
| <b>product functions / security</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• ACL - port/MAC-based</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• broadcast/multicast/unicast limiter</li> </ul>                               | Yes |
| <ul style="list-style-type: none"> <li>• broadcast blocking</li> </ul>  | Yes |
| protocol / is supported   |     |
| <ul style="list-style-type: none"> <li>• SSH</li> </ul>   | Yes |
| <b>product functions / time</b>   |     |
| product function  |     |
| <ul style="list-style-type: none"> <li>• SICLOCK support</li> </ul>   | Yes |
| protocol / is supported   |     |
| <ul style="list-style-type: none"> <li>• NTP</li> </ul>   | Yes |
| <ul style="list-style-type: none"> <li>• SNTP</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• IEEE 1588 profile default</li> </ul>   | Yes |

**standards, specifications, approvals**

|   |  |
|---|--|
| standard  |  |
| <ul style="list-style-type: none"> <li>• for FM</li> </ul>                        | FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 |
| <ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>  | UL 60950-1, CSA C22.2 No. 60950-1  |
| <ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>      | EN 61000-6-4:2007 (Class A)  |
| <ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>     | EN 61000-6-2:2005  |
| MTBF  | 40 a   |
| reference code  |  |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> </ul>      | KF   |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul> | KFE  |

**standards, specifications, approvals / CE**

|   |     |
|---|-----|
| certificate of suitability / CE marking | Yes |
|---|-----|

**standards, specifications, approvals / hazardous environments**

|  |   |
|--|---|
| standard / for hazardous zone  | EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X   |
| <ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>  | UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4 |
| certificate of suitability   |   |
| <ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard</li> </ul>              | Yes   |
| <ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard / as marking</li> </ul> | Ex nA IIC T4 Gc   |

**standards, specifications, approvals / other**

|   |                                      |
|---|--------------------------------------|
| certificate of suitability  | EN 61000-6-2:2005, EN 61000-6-4:2007 |
| <ul style="list-style-type: none"> <li>• C-Tick</li> </ul>  | Yes                                  |
| <ul style="list-style-type: none"> <li>• KC approval</li> </ul>                                     | Yes                                  |
| <ul style="list-style-type: none"> <li>• railway application in accordance with EN 50155</li> </ul> | No                                   |

**standards, specifications, approvals / marine classification**

|   |     |
|---|-----|
| Marine classification association   |     |
| <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul> | Yes |
| <ul style="list-style-type: none"> <li>• French marine classification society (BV)</li> </ul>     | Yes |
| <ul style="list-style-type: none"> <li>• Det Norske Veritas (DNV)</li> </ul>                      | No  |
| <ul style="list-style-type: none"> <li>• Germanische Lloyd (GL)</li> </ul>                        | No  |
| <ul style="list-style-type: none"> <li>• DNV GL</li> </ul>  | Yes |
| <ul style="list-style-type: none"> <li>• Korean Register of Shipping (KRS)</li> </ul>             | Yes |
| <ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>             | Yes |
| <ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (NK)</li> </ul>                      | Yes |
| <ul style="list-style-type: none"> <li>• Polski Rejestr Statkow (PRS)</li> </ul>                  | No  |
| <ul style="list-style-type: none"> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>  | No  |

**further information / internet links**

|   |   |
|---|---|
| internet link   |   |
| <ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul> | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>   |
| <ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>          | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| <ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>                     | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| <ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>   | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| <ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>                    | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| <ul style="list-style-type: none"> <li>• to website: CAx-Download-Manager</li> </ul>              | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| <ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>           | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

**security information**

|                      |  |
|----------------------|--|
| security information | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit <a href="https://www.siemens.com/industrialsecurity">https://www.siemens.com/industrialsecurity</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, |
|----------------------|--|

Approvals / Certificates

EMC For use in hazardous locations



[ATEX-Zone 2-Declaration](#)



[EM](#)

[CCC-Ex](#)



Declaration of Conformity Test Certificates Marine / Shipping



[Manufacturer Declaration](#)



[Type Test Certificates/Test Report](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



last modified:

9/22/2023