SIEMENS

Data sheet

6GK5992-4SA00-8AA0

product type designation

MM992-4CU

SCALANCE X accessory; Media module MM992-4CU; 4x 1000 Mbit/s RJ45 ports, electrical; without securing collar.



number of electrical connections • for network components or terminal equipment /	4 4 4
number of electrical connections • for network components or terminal equipment /	4
for network components or terminal equipment /	
maximum	4
number of 10/100/1000 Mbit/s RJ45 ports	
type of electrical connection	
for network components or terminal equipment	RJ45
ambient conditions	
ambient temperature	
during operation	0 60 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
P. COLOR	IP20
design, dimensions and weights	
design	Media module
width	120.3 mm
height	22.3 mm
depth	275.5 mm
net weight	0.3 kg
fastening method	latched
• installation in media module slot	Yes
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
	EN 61000-6-4 (Class A)
	EN 61000-6-2
•	EN 61000-6-2:2005, EN 61000-6-4:2007
CE marking	Yes
C-Tick	Yes
KC approval	Yes
CCC / for hazardous zone according to GB standard	Yes
CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
• E1 approval	No
Marine classification association	
• French marine classification society (BV)	Yes

further information / internet links internet link • to web page: selection aid TIA Selection Tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net • to website: Industrial communication • to website: Industry Mall https://mall.industry.siemens.com • to website: Information and Download Center http://www.siemens.com/industry/infocenter • to website: Image database http://automation.siemens.com/bilddb • to website: CAx-Download-Manager http://www.siemens.com/cax https://support.industry.siemens.com • to website: Industry Online Support

last modified: 8/11/2023 🖸