SIEMENS

Data sheet

6GK7243-1JX30-0XE0

product type designation



CP 1243-1 DNP3

******** spare part ******* communications processor CP 1243-1 DNP3 for connection of SIMATIC S7-1200 to control center with DNP3 protocol

transfer rate	
transfer rate	
at the 1st interface	10 100 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	1
number of electrical connections	
 at the 1st interface / acc. to Industrial Ethernet 	1
for power supply	0
type of electrical connection	
 at the 1st interface / acc. to Industrial Ethernet 	RJ45 port
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
consumed current	
from backplane bus / at DC / at 5 V / typical	0.25 A
power loss [W]	1.25 W
ambient conditions	
ambient temperature	
 for vertical installation / during operation 	-20 +60 °C
 for horizontally arranged busbars / during operation 	-20 +70 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	110 mm
depth	75 mm
net weight	0.122 kg
fastening method	
 35 mm top hat DIN rail mounting 	Yes
wall mounting	Yes
product features, product functions, product components / general	
number of units	
• per CPU / maximum	3

performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	like CPU
performance data / IT functions	
number of possible connections	
as email client / maximum	1
performance data / telecontrol	
suitability for use	
node station	No
substation	Yes
TIM control center	No
control center connection	control center with DNP3 function
 by means of a permanent connection 	supported
• note	Connection to SCADA system using DNP3 services
protocol / is supported	
• DNP3	Yes
• IEC 60870-5	No
product function / data buffering if connection is aborted	Yes; 64,000 values
number of data points per station / maximum	200
performance data / teleservice	
diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
product function	
 program download with SIMATIC STEP 7 	Yes
remote firmware update	Yes
product functions / management, configuration, engineering	ng
configuration software	
• required	STEP 7 Basic/Professional
product functions / time	
protocol / is supported	
• NTP	No
time synchronization	
from control center	Yes
further information / internet-Links	
Internet-Link	
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	8/3/2021 🖸