

product type designation

CP 342-5 FO

Communications processor CP 342-5 FO for connection of SIMATIC S7-300 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication



transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	0
number of electrical connections	
<ul style="list-style-type: none"> for power supply 	1
number of optical interfaces / at the 1st interface / acc. to PROFIBUS	2
design of the optical interface / at the 1st interface / acc. to PROFIBUS	Duplex socket
type of electrical connection	
<ul style="list-style-type: none"> for power supply 	4-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	24 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical 	0.15 A
<ul style="list-style-type: none"> from external supply voltage / at DC / at 24 V / typical 	0.25 A
power loss [W]	6 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module
width	40 mm
height	125 mm

depth	120 mm
net weight	0.3 kg
fastening method	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	
product features, product functions, product components / general	
number of units	4
<ul style="list-style-type: none"> • per CPU / maximum 	
wire length	300 m
<ul style="list-style-type: none"> • for PCF FOC / maximum • for POF FOC / maximum 	50 m
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
data volume	240 byte
<ul style="list-style-type: none"> • as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	
performance data / PROFIBUS DP	
service / as DP master	Yes
<ul style="list-style-type: none"> • DPV0 	
number of DP slaves	124
<ul style="list-style-type: none"> • on DP master / operable 	
data volume	2160 byte
<ul style="list-style-type: none"> • of the address range of the inputs / as DP master / total • of the address range of the outputs / as DP master / total • of the address range of the inputs / per DP slave • of the address range of the outputs / per DP slave • of the address range of the diagnostic data / per DP slave 	2160 byte 2160 byte 244 byte 244 byte 240 byte
service / as DP slave	Yes
<ul style="list-style-type: none"> • DPV0 	
data volume	240 byte
<ul style="list-style-type: none"> • of the address range of the inputs / as DP slave / total • of the address range of the outputs / as DP slave / total 	240 byte 240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	16
<ul style="list-style-type: none"> • maximum 	
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	32
<ul style="list-style-type: none"> • without DP / maximum • with DP / maximum 	28
performance data / telecontrol	
protocol / is supported	No
<ul style="list-style-type: none"> • TCP/IP 	
product functions / management, configuration, engineering	
configuration software	STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher
<ul style="list-style-type: none"> • required 	
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter

- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

8/3/2021 